

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :				
Product line		: Premium Efficiency Three-Phase	Product code :	13989587
Frame	: W56C	Cooling method	: IC01 - ODP	
Insulation class	: F	Mounting	: F-1	
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)	
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line	
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 8.8 kg	
		Moment of inertia (J)	: 0.0019 kgm ²	
Output [HP]	0.5			
Poles	4			
Frequency [Hz]	60			
Rated voltage [V]	575			
Rated current [A]	0.631			
L. R. Amperes [A]	4.04			
LRC [A]	6.4x(Code K)			
No load current [A]	0.426			
Rated speed [RPM]	1735			
Slip [%]	3.61			
Rated torque [kgfm]	0.209			
Locked rotor torque [%]	250			
Breakdown torque [%]	320			
Service factor	1.15			
Temperature rise	80 K			
Locked rotor time	41s (cold) 23s (hot)			
Noise level ²	50.0 dB(A)			
Efficiency (%)	25%			
	50%	70.0		
	75%	75.5		
	100%	78.5		
Power Factor	25%			
	50%	0.53		
	75%	0.66		
	100%	0.75		
Bearing type	: Drive end 6203 ZZ Non drive end 6202 ZZ	Foundation loads		
Sealing	: Without Without Bearing Seal Bearing Seal	Max. traction : 17 kgf		
		Max. compression : 26 kgf		
Lubrication interval	: - -			
Lubricant amount	: - -			
Lubricant type	: Mobil Polyrex EM			
Notes				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked
Performed by			Page 1 / 2	Revision
Checked by				
Date	11/05/2022			


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Premium Efficiency Three-Phase Product code : 13989587




Performance : 575 V 60 Hz 4P

Rated current : 0.631 A
 LRC : 6.4
 Rated torque : 0.209 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 320 %
 Rated speed : 1735 rpm

Moment of inertia (J) : 0.0019 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by		<div>Page 2 / 2</div> <div>Revision</div>		
Checked by				
Date	11/05/2022			



Color Munsell N 1 matte black									
Painting plan 207N									
Mounting B34D									