

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11992396

Frame	: 182/4TC	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 7.01 A	Protection degree	: IP55
L. R. Amperes	: 57.5 A	Cooling method	: IC411 - TEFC
LRC	: 8.2x(Code J)	Mounting	: F-1
No load current	: 2.32 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 3485 rpm	Noise level <sup>2</sup>	: 66.0 dB(A)
Slip	: 3.19 %	Starting method	: Direct On Line
Rated torque	: 1.56 kgfm	Approx. weight <sup>3</sup>	: 46.3 kg
Locked rotor torque	: 270 %		
Breakdown torque	: 330 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0095 kgm <sup>2</sup>		
Design	: A		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	88.5	89.5	89.5	Max. traction	: 85 kgf
Power Factor	0.75	0.84	0.88	Max. compression	: 131 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.4	9.4	8.7	5.3	3.4	2.1	1.3

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6207 ZZ	6206 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	14/07/2025			

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency  
Three-Phase

Product code : 11992396



Performance : 575 V 60 Hz 2P

Rated current : 7.01 A  
LRC : 8.2  
Rated torque : 1.56 kgfm  
Locked rotor torque : 270 %  
Breakdown torque : 330 %  
Rated speed : 3485 rpm

Moment of inertia (J) : 0.0095 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.25  
Temperature rise : 80 K  
Design : A

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2	Revision
Checked by					
Date	14/07/2025				

