DATA SHEET

Single Phase Induction Motor - Squirrel Cage

Customer :

Product line	: Rolled Steel JM Pump Single-Phase	Product code :	18298167

Frame	: 213/5JM	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Frequency	: 60 Hz	Duty cycle	: Cont.(S1)
Rated voltage	: 208-230/460 V	Ambient temperature	: -20°C to +40°C
Poles	: 2	Altitude	: 1000 m.a.s.l.
Rated current	: 32.5-29.4/14.7 A	Protection degree	: IP55
	: 7.1x(Code H)	Cooling method	: IC411 - TEFC
Rated speed	: 3515 rpm	Mounting	: F-1
Rated torque	: 1.55 kgfm	Rotation[1]	: Both (CW and CCW)
Insulation class	: F	Noise level[2]	: 75.0 dB(A)
Service factor	: 1.15	Starting method	: Direct On Line
Moment of inertia (J)	: 0.0205 kgm²	Approx. weight[3]	: 68.1 kg
Design	: L		

Output	50%	75%	100%
Efficiency (%)	78.5	82.5	84.0
Power Factor	0.96	0.97	0.97

Foundation loads

Max. traction	: 43 kgf
Max. compression	: 111 kgf

		Drive end	Non drive end
Bearing type	:	6209 ZZ	6206 ZZ
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	02/04/2026		1 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage

Customer :

Product line : Rolled Steel JM Pump Single-Phase


Product code : 18298167





Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	02/04/2026		2 / 2	


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice







DE Shaft End



EUNC 3/8"-16 WEG WPR-7309

Mounting MARKET F-1/B34R(D)

Mounting B34D

7.5 HP 02 Poles 60 Hz | A

Scale 2 : 13

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
			HYBRISUSER				00

EXECUTED	HYBRISUSER
CHECKED	
RELEASED	
REL. DATE	

SINGLE PH. MOTOR ROLLED STEEL JM
FRAME 213/5JM IP55 TEFC

PREVIEW

WDD 00

SHEET 1 / 1

Dimensions in inches

A3

WEG's property. Forbidden reproduction without previous authorization.