

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line		: W22 NEMA Premium Efficiency Three-Phase		Product code :		12984344
Frame	:	254/6TC		Locked rotor time	:	54s (cold) 30s (hot)
Output	:	7.5 HP (5.5 kW)		Temperature rise	:	80 K
Frequency	:	60 Hz		Duty cycle	:	Cont.(S1)
Rated voltage	:	575 V		Ambient temperature	:	-20°C to +40°C
Poles	:	8		Altitude	:	1000 m.a.s.l.
Rated current	:	9.02 A		Protection degree	:	IP55
	:	5.3x(Code H)		Cooling method	:	IC411 - TEFC
Rated speed	:	880 rpm		Mounting	:	F-1
Rated torque	:	6.19 kgfm		Rotation <sup>1</sup>	:	Both (CW and CCW)
Insulation class	:	F		Noise level <sup>2</sup>	:	54.0 dB(A)
Service factor	:	1.25		Starting method	:	Direct On Line
Moment of inertia (J)	:	0.1867 kgm <sup>2</sup>		Approx. weight <sup>3</sup>	:	125 kg
Design	:	B				
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	85.5	87.5	87.5	Max. traction	:	181 kgf
Power Factor	0.50	0.63	0.70	Max. compression	:	305 kgf
Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
13.7	11.9	12.0	8.0	6.0	4.8	3.7
			<u>Drive end</u>	<u>Non drive end</u>		
Bearing type	:	6309 C3		6209 C3		
Sealing	:	V'Ring		V'Ring		
Lubrication interval	:	20000 h		20000 h		
Lubricant amount	:	13 g		9 g		
Lubricant type	:	Mobil Polyrex EM				
Notes						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	23/03/2026				1 / 2	


# LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :


Product line : W22 NEMA Premium Efficiency Three-Phase      Product code : 12984344



Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2		Revision
Checked by				
Date				



Without vertical jackscrews  
 Color RAL 5009  
 Painting plan 203A  
 Mounting NEMA F-1  
 Mounting B34D



7.5 HP 08 Poles 60 Hz										A	
Scale 1 : 8											
HYBRISUSER										00	
ECM	LOC	SUMMARY OF MODIFICATIONS					EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	HYBRISUSER	THREE PH. MOTOR W22 NEMA PREM. EFF.					PREVIEW		WDD 00		
CHECKED		FRAME 254/6TC IP55 TEFC					SHEET 1 / 1				
RELEASED											
REL. DATE											