

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :				
Product line		: Jet Pump - J type Three-Phase	Product code :	14103958
Frame	: W56J	Cooling method	: IC01 - ODP	
Insulation class	: F	Mounting	: F-1	
Duty cycle	: Cont.(S1)	Rotation ¹	: CCW	
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line	
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 11.5 kg	
Design	: A	Moment of inertia (J)	: 0.0014 kgm ²	
Output [HP]	1.5			
Poles	2			
Frequency [Hz]	60			
Rated voltage [V]	575			
Rated current [A]	1.69			
L. R. Amperes [A]	14.9			
LRC [A]	8.8x(Code L)			
No load current [A]	0.960			
Rated speed [RPM]	3450			
Slip [%]	4.17			
Rated torque [kgfm]	0.316			
Locked rotor torque [%]	400			
Breakdown torque [%]	430			
Service factor	1.30			
Temperature rise	80 K			
Locked rotor time	23s (cold) 13s (hot)			
Noise level ²	62.0 dB(A)			
Efficiency (%)	25%			
	50%	78.5		
	75%	82.5		
	100%	84.0		
Power Factor	25%			
	50%	0.59		
	75%	0.72		
	100%	0.78		
Bearing type	: Drive end 6203 2RS Non drive end 6202 2RS	Foundation loads		
Sealing	: Without Bearing Seal Without Bearing Seal	Max. traction : 37 kgf		
		Max. compression : 49 kgf		
Lubrication interval	: -			
Lubricant amount	: -			
Lubricant type	: Mobil Polyrex EM			
Notes				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 1 / 2
Checked by				
Date	11/05/2022			
Revision				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Jet Pump - J type Three-Phase

Product code : 14103958



Performance : 575 V 60 Hz 2P

Rated current : 1.69 A
 LRC : 8.8
 Rated torque : 0.316 kgfm
 Locked rotor torque : 400 %
 Breakdown torque : 430 %
 Rated speed : 3450 rpm

Moment of inertia (J) : 0.0014 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.30
 Temperature rise : 80 K
 Design : A

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2	Revision
Checked by					
Date	11/05/2022				

