

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11431671

Frame	: 364/5TS	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 374 kg
Protection degree	: IP56	Moment of inertia (J)	: 0.4485 kgm ²
Design	: B		

Output [HP]	60	50	50	50	60	60	60
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	460	380	400	415	380	400	415
Rated current [A]	67.0	66.6	63.7	62.1	81.3	77.6	74.8
L. R. Amperes [A]	429	406	433	447	407	435	449
LRC [A]	6.4x(Code G)	6.1x(Code F)	6.8x(Code G)	7.2x(Code H)	5.0x(Code D)	5.6x(Code F)	6.0x(Code F)
No load current [A]	15.0	15.0	16.2	17.4	15.0	16.2	17.4
Rated speed [RPM]	3550	2945	2950	2955	2935	2940	2945
Slip [%]	1.39	1.83	1.67	1.50	2.17	2.00	1.83
Rated torque [kgfm]	12	12	12	12	14	14	14
Locked rotor torque [%]	190	180	210	220	150	170	180
Breakdown torque [%]	250	240	270	290	200	220	240
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	25s (cold) 14s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)
Noise level ²	79.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)
Efficiency (%)	25%						
	50%	91.7	92.1	91.7	91.6	92.4	92.4
	75%	93.0	92.8	92.8	92.9	93.0	93.0
	100%	93.6	92.8	93.1	93.1	92.4	93.0
Power Factor	25%						
	50%	0.81	0.81	0.79	0.76	0.85	0.83
	75%	0.88	0.88	0.87	0.85	0.90	0.89
	100%	0.90	0.91	0.90	0.89	0.91	0.90

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	7.4	8.4	8.0	8.0	8.9	8.2	8.2
	P2 (0,5;1,0)	5.8	6.8	6.4	6.4	7.3	6.5	6.5
	P3 (0,25;1,0)	5.1	6.1	5.7	5.7	6.5	5.8	5.8
	P4 (0,9;0,5)	3.7	4.1	4.0	4.0	4.4	4.0	4.0
	P5 (0,5;0,5)	2.3	2.6	2.5	2.5	2.8	2.5	2.5
	P6 (0,5;0,25)	1.4	1.7	1.6	1.6	1.8	1.6	1.6
	P7 (0,25;0,25)	0.9	1.1	1.0	1.0	1.2	1.0	1.0

Bearing type	: 6314 C3	Non drive end	6314 C3	Foundation loads	
Sealing	: Inpro/Seal	Inpro/Seal		Max. traction	: 207 kgf
Lubrication interval	: 4000 h	4000 h		Max. compression	: 589 kgf
Lubricant amount	: 27 g	27 g			
Lubricant type	: Mobil Polyrex EM				

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	24/09/2026		Page 1 / 9	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Notes

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 9	Revision
Checked by					
Date	24/09/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431671



Performance : 460 V 60 Hz 2P

Rated current : 67.0 A
LRC : 6.4
Rated torque : 12 kgfm
Locked rotor torque : 190 %
Breakdown torque : 250 %
Rated speed : 3550 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	24/09/2026			

Page	Revision
3 / 9	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431671



Performance : 380 V 50 Hz 2P IE2

Rated current : 66.6 A
LRC : 6.1
Rated torque : 12 kgfm
Locked rotor torque : 180 %
Breakdown torque : 240 %
Rated speed : 2945 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431671



Performance : 400 V 50 Hz 2P IE2

Rated current : 63.7 A
LRC : 6.8
Rated torque : 12 kgfm
Locked rotor torque : 210 %
Breakdown torque : 270 %
Rated speed : 2950 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9Revision		
Checked by				
Date	24/09/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431671



Performance : 415 V 50 Hz 2P IE2

Rated current : 62.1 A
LRC : 7.2
Rated torque : 12 kgfm
Locked rotor torque : 220 %
Breakdown torque : 290 %
Rated speed : 2955 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 6 / 9Revision		
Checked by				
Date	24/09/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431671



Performance : 380 V 50 Hz 2P IE1

Rated current : 81.3 A
LRC : 5.0
Rated torque : 14 kgfm
Locked rotor torque : 150 %
Breakdown torque : 200 %
Rated speed : 2935 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 7 / 9Revision		
Checked by				
Date	24/09/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431671



Performance : 400 V 50 Hz 2P IE2

Rated current : 77.6 A
LRC : 5.6
Rated torque : 14 kgfm
Locked rotor torque : 170 %
Breakdown torque : 220 %
Rated speed : 2940 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 8 / 9	Revision
Checked by					
Date	24/09/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431671




Performance : 415 V 50 Hz 2P IE2

Rated current : 74.8 A
LRC : 6.0
Rated torque : 14 kgfm
Locked rotor torque : 180 %
Breakdown torque : 240 %
Rated speed : 2945 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 9 / 9		
Checked by				
Date	24/09/2026			
		Revision		



60 HP 02 Poles 60 Hz										A
						Scale				1 : 11
					HYBRISUSER					00
ECM		LOC		SUMMARY OF MODIFICATIONS		EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	HYBRISUSER		THREE PH. MOTOR IEEE 841 W22 NEMA PREM. EFF. FRAME 364/5TS IP56 TEFC			PREVIEW WDD 00				
CHECKED										
RELEASED										
REL. DATE										
						SHEET		1 / 1		

WEG's property. Forbidden reproduction without previous authorization.

Dimensions in inches

A3