

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium Efficiency Three-Phase Product code : 14353304

Frame	: 213/5T	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 92.8 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.0620 kgm ²
Design	: B		

Output [HP]	5	5	5	5
Poles	6	6	6	6
Frequency [Hz]	60	50	50	50
Rated voltage [V]	230/460	380	400	415
Rated current [A]	13.7/6.83	8.20	7.82	7.65
L. R. Amperes [A]	92.9/46.4	45.1	47.7	49.7
LRC [A]	6.8x(Code J)	5.5x(Code G)	6.1x(Code H)	6.5x(Code J)
No load current [A]	6.90/3.45	3.41	3.68	3.90
Rated speed [RPM]	1170	960	965	970
Slip [%]	2.50	4.00	3.50	3.00
Rated torque [kgfm]	3.10	3.78	3.76	3.74
Locked rotor torque [%]	170	150	160	190
Breakdown torque [%]	260	215	220	250
Service factor	1.15	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K
Locked rotor time	102s (cold) 57s (hot)	54s (cold) 30s (hot)	54s (cold) 30s (hot)	54s (cold) 30s (hot)
Noise level ²	55.0 dB(A)	53.0 dB(A)	53.0 dB(A)	53.0 dB(A)
Efficiency (%)	25%	88.2	89.8	89.1
	50%	88.5	88.5	88.5
	75%	89.5	88.5	88.5
	100%	89.5	86.8	87.5
Power Factor	25%	0.34	0.40	0.37
	50%	0.58	0.65	0.61
	75%	0.70	0.75	0.73
	100%	0.76	0.79	0.78

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	11.1	14.4	13.5	12.3
	P2 (0,5;1,0)	9.1	11.8	11.1	10.1
	P3 (0,25;1,0)	8.8	11.4	10.8	9.8
	P4 (0,9;0,5)	5.8	7.5	7.1	6.4
	P5 (0,5;0,5)	4.0	5.2	4.9	4.5
	P6 (0,5;0,25)	2.9	3.7	3.5	3.2
	P7 (0,25;0,25)	2.1	2.7	2.6	2.3

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads	
Bearing type	: 6308 2RS	6207 2RS	Max. traction	: 126 kgf
Sealing	: Oil Seal	Lip Seal	Max. compression	: 219 kgf
Lubrication interval	: -	-		
Lubricant amount	: -	-		
Lubricant type	: Mobil Polyrex EM			

This revision replaces and cancel the previous one, which must be eliminated.
 (1) Looking the motor from the shaft end.
 (2) Measured at 1m and with tolerance of +3dB(A).
 (3) Approximate weight subject to changes after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/10/2024			

Page 1 / 7
Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 15.1A SF 1.15 SFA 17.4A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 7		Revision
Checked by					
Date	28/10/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection				
ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 7	Revision
Checked by					
Date	28/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA
Premium Efficiency Three-Phase

Product code : 14353304



Performance : 230/460 V 60 Hz 6P

Rated current : 13.7/6.83 A
LRC : 6.8
Rated torque : 3.10 kgfm
Locked rotor torque : 170 %
Breakdown torque : 260 %
Rated speed : 1170 rpm

Moment of inertia (J) : 0.0620 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 7	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA
Premium Efficiency Three-Phase

Product code : 14353304



Performance : 380 V 50 Hz 6P IE3

Rated current	: 8.20 A	Moment of inertia (J)	: 0.0620 kgm ²
LRC	: 5.5	Duty cycle	: Cont.(S1)
Rated torque	: 3.78 kgfm	Insulation class	: F
Locked rotor torque	: 150 %	Service factor	: 1.00
Breakdown torque	: 215 %	Temperature rise	: 80 K
Rated speed	: 960 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 7Revision		
Checked by				
Date	28/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA
Premium Efficiency Three-Phase

Product code : 14353304



Performance : 400 V 50 Hz 6P IE3

Rated current : 7.82 A
LRC : 6.1
Rated torque : 3.76 kgfm
Locked rotor torque : 160 %
Breakdown torque : 220 %
Rated speed : 965 rpm

Moment of inertia (J) : 0.0620 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 7	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA
Premium Efficiency Three-Phase

Product code : 14353304



Performance : 415 V 50 Hz 6P IE3

Rated current	: 7.65 A	Moment of inertia (J)	: 0.0620 kgm ²
LRC	: 6.5	Duty cycle	: Cont.(S1)
Rated torque	: 3.74 kgfm	Insulation class	: F
Locked rotor torque	: 190 %	Service factor	: 1.00
Breakdown torque	: 250 %	Temperature rise	: 80 K
Rated speed	: 970 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 7 / 7		
Checked by				
Date	28/10/2024			
		Revision		

