

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 NEMA Premium Efficiency Three-Phase Product code : 14448253

Frame	: 444/5T	Locked rotor time	: 25s (cold) 14s (hot)
Output	: 200 HP (150 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 187 A	Protection degree	: IP23
L. R. Amperes	: 1236 A	Cooling method	: IC01 - ODP
LRC	: 6.6x(Code G)	Mounting	: F-1
No load current	: 69.2 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1783 rpm	Noise level ²	: 78.0 dB(A)
Slip	: 0.94 %	Starting method	: Direct On Line
Rated torque	: 81.4 kgfm	Approx. weight ³	: 630 kg
Locked rotor torque	: 210 %		
Breakdown torque	: 250 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 1.96 kgm ²		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	95.4	95.8	95.8	Max. traction	: 1465 kgf
Power Factor	0.72	0.80	0.84	Max. compression	: 2095 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6319 C3	6212 Z C3
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	45 g	13 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	28/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 NEMA Premium Efficiency
Three-Phase

Product code : 14448253






Performance : 575 V 60 Hz 4P



Rated current : 187 A
LRC : 6.6
Rated torque : 81.4 kgfm
Locked rotor torque : 210 %
Breakdown torque : 250 %
Rated speed : 1783 rpm

Moment of inertia (J) : 1.96 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					



Color RAL 5009
Painting plan 203A
Mounting NEMA F-1
Mounting B3R(D)

200 HP 04 Poles 60 Hz										A
										1:10
										00
ECM	LOC	SUMMARY OF MODIFICATIONS				EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	HYBRISUSER		THREE PH. MOTOR W40 NEMA PREM. EFF. FRAME 444/5T IP23 ODP				<div> <div>PREVIEW</div> <div>WDD 00</div> </div>			
CHECKED										
RELEASED										
REL. DATE		WMO	Jaragua do Sul		Product Engineering		SHEET	1 / 1		