

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC - Nema Premium Efficiency

Frame	: 213/5T	Locked rotor time	: 46 s (hot) 83 s (cold)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 575 V	Altitude	: 3280 ft
Rated current	: 3.25 A	Protection degree	: IP55
L. R. Amperes	: 21.1 A	Cooling method	: IC411 - TEFC
LRC	: 6.5	Mounting	: F-1/B3R(D)
No load current	: 1.68 A	Rotation ¹	: Both
Rated speed	: 1180 rpm	Noise level ²	: 55.0 dB(A)
Slip	: 1.67 %	Vibration class	: A
Rated torque	: 13.2 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 200 %	Approx. weight ³	: 129 lb
Pull up torque	: 170 %	Painting plan	: 207N
Breakdown torque	: 250 %	Color	: MUNSELL N 1 - MATTE
Insulation class	: F	Design	: B
Service factor	: 1.15		
Moment of inertia (J)	: 1.08 sq.ft.lb		

Output	50%	75%	100%
Efficiency (%)	85.5	88.5	89.5
Power Factor	0.60	0.70	0.76

Load type	: -
Load torque	: -
Load inertia (J=GD ² /4)	: -

	Drive end	Non drive end
Bearing type #1	6208-ZZ	6206-ZZ
Bearing type #2	-	-
Lubrication interval	-	-
Lubricant amount #1	-	-
Lubricant amount #2	-	-
Lubricant type	MOBIL POLYREX EM	

Foundation loads	
Max. traction	:
Max. compression	:

Notes

See notes on page 2.

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.1	8.9	8.1	6.2	4.2	3.1	2.3

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq			1859923533	
Checked by	AUTOMATICO			Page	Rev.
Date	12/06/2026			1 / 2	0

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC - Nema Premium Efficiency

Thermal protection ID	Application	Type	Quantity	Sensing Temperature
-----------------------	-------------	------	----------	---------------------

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight, subject to be changed after manufacturing process.	These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.
---	---

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq		1859923533		
Checked by	AUTOMATICO		Page	Rev.	
Date	12/06/2026		2 / 2	0	

