DATA SHEET

Single Phase Induction Motor - Squirrel Cage

Customer :

Product line : Centrifugal Pump Single-Phase Start Capacitor

Product code : 10504701

Frame	: D56J	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 115/208-230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 3.34/6.40-1.67 A	Protection degree	: IP55
L. R. Amperes	: 23.4/44.8-11.7 A	Cooling method	: IC411 - TEFC
LRC	: 7.0x(Code M)	Mounting	: F-1
No load current	: 2.35/1.01-1.17 A	Rotation¹	: CCW
Rated speed	: 3500 rpm	Vibration	: Not Applicable
Slip	: 2.78 %	Starting method	: Direct On Line
Rated torque	: 0 kgfm	Approx. weight³	: 14.5 kg
Locked rotor torque	: 320 %	Painting plan	: 207N (ISO 12944 - C2)
Breakdown torque	: 280 %	Color	: Munsell N 1 - Matte
Insulation class	: B		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0022 kgm²		

Output	50%	75%	100%
Efficiency (%)	55.0	63.0	67.0
Power Factor	0.56	0.67	0.75

Foundation loads

Max. traction	: 11 kgf
Max. compression	: 26 kgf

		Drive end	Non drive end
Bearing type	:	6204 2RS	6202 2RS
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	08/10/2026		1 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage

Customer :

Product line : Centrifugal Pump Single-Phase Start Capacitor

Product code : 10504701



Performance	: 115/208-230 V 60 Hz 2P

Rated current	: 3.34/6.40-1.67 A	Moment of inertia (J)	: 0.0022 kgm²
LRC	: 7.0	Duty cycle	: Cont.(S1)
Rated torque	: 0 kgfm	Insulation class	: B
Locked rotor torque	: 320 %	Service factor	:
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 3500 rpm		

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	08/10/2026		2 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice