

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Explosion Proof Standard Efficiency Three-Phase Product code : 10627444

Frame	: A56CEX	Locked rotor time	: 27s (cold) 15s (hot)
Output	: 0.33 HP (0.25 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 0.520 A	Protection degree	: IP44
L. R. Amperes	: 2.70 A	Cooling method	: IC411 - TEFC
LRC	: 5.2x(Code K)	Mounting	: F-1
No load current	: 0.400 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1750 rpm	Noise level ²	: 50.0 dB(A)
Slip	: 2.78 %	Vibration	: A
Rated torque	: 0 kgfm	Starting method	: Direct On Line
Locked rotor torque	: 240 %	Approx. weight ³	: 13.6 kg
Breakdown torque	: 300 %		: 207N (ISO 12944 - C2)
Insulation class	: B		: RAL 7022
Service factor	: 1.15		
Moment of inertia (J)	: 0.0026 kgm ²		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	66.0	72.0	74.0	Max. traction	: 6 kgf
Power Factor	0.43	0.50	0.65	Max. compression	: 20 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6203 ZZ	6203 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3 Revision		
Checked by				
Date	01/10/2026			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	130 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 3	
Date	01/10/2026				


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Explosion Proof Standard Efficiency Three-Phase Product code : 10627444



Performance : 575 V 60 Hz 4P

Rated current : 0.520 A
LRC : 5.2
Rated torque : 0 kgfm
Locked rotor torque : 240 %
Breakdown torque : 300 %
Rated speed : 1750 rpm

Moment of inertia (J) : 0.0026 kgm²
Duty cycle : Cont.(S1)
Insulation class : B
Service factor : 1.15
Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3Revision		
Checked by				
Date	01/10/2026			