

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump NEMA Premium Efficiency Three-Phase Product code : 10781668

Frame	: 286JM	Cooling method	: IC01 - ODP
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 193 kg
Protection degree	: IP23	Moment of inertia (J)	: 0.2063 kgm ²
Design	: B		

Output [HP]	30	25	25	25	30	30	30
Poles	4	4	4	4	4	4	4
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	69.8/34.9	35.7	34.7	34.3	42.9	41.4	40.1
L. R. Amperes [A]	461/230	246	250	244	215	232	245
LRC [A]	6.6x(Code G)	6.9x(Code H)	7.2x(Code H)	7.1x(Code H)	5.0x(Code E)	5.6x(Code F)	6.1x(Code G)
No load current [A]	24.2/12.1	12.0	14.0	13.5	11.7	12.6	13.2
Rated speed [RPM]	1770	1470	1470	1475	1460	1465	1468
Slip [%]	1.67	2.00	2.00	1.67	2.67	2.33	2.13
Rated torque [kgfm]	12.3	12.3	12.3	12.3	14.9	14.9	14.8
Locked rotor torque [%]	240	220	250	270	170	190	210
Breakdown torque [%]	270	240	270	300	200	220	240
Service factor	1.15	1.15	1.15	1.15	1.15	1.15	1.15
Temperature rise	80 K	80 K	80 K	80 K	80 K	80 K	80 K
Locked rotor time	25s (cold) 14s (hot)	30s (cold) 17s (hot)	27s (cold) 15s (hot)	25s (cold) 14s (hot)	30s (cold) 17s (hot)	27s (cold) 15s (hot)	25s (cold) 14s (hot)
Noise level ²	63.0 dB(A)						
Efficiency (%)	25%						
	50%	93.6	92.2	92.2	92.2	91.7	91.7
	75%	94.1	92.6	92.6	92.6	92.4	92.4
	100%	94.1	92.6	92.6	92.6	91.7	92.4
Power Factor	25%						
	50%	0.70	0.70	0.66	0.63	0.74	0.70
	75%	0.80	0.80	0.78	0.75	0.83	0.80
	100%	0.84	0.85	0.83	0.81	0.85	0.83

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads
Bearing type	: 6311 Z C3	6211 Z C3	Max. traction : 413 kgf
Sealing	: Without	Without	Max. compression : 606 kgf
	Bearing Seal	Bearing Seal	
Lubrication interval	: 20000 h	20000 h	
Lubricant amount	: 18 g	11 g	
Lubricant type	: Mobil Polyrex EM		

Notes

USABLE @208V 78.3A SF 1.15 SFA 90.0A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	24/10/2024			

Page 1 / 8
Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump NEMA
Premium Efficiency Three-Phase

Product code : 10781668



Performance : 230/460 V 60 Hz 4P

Rated current : 69.8/34.9 A
LRC : 6.6
Rated torque : 12.3 kgfm
Locked rotor torque : 240 %
Breakdown torque : 270 %
Rated speed : 1770 rpm

Moment of inertia (J) : 0.2063 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 8	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump NEMA
Premium Efficiency Three-Phase

Product code : 10781668



Performance : 380 V 50 Hz 4P IE3

Rated current : 35.7 A
LRC : 6.9
Rated torque : 12.3 kgfm
Locked rotor torque : 220 %
Breakdown torque : 240 %
Rated speed : 1470 rpm

Moment of inertia (J) : 0.2063 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 8Revision		
Checked by				
Date	24/10/2024			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : Close Coupled Pump NEMA
Premium Efficiency Three-Phase

Product code : 10781668

LOAD PERFORMANCE CURVE



Performance : 400 V 50 Hz 4P IE3

Rated current : 34.7 A
LRC : 7.2
Rated torque : 12.3 kgfm
Locked rotor torque : 250 %
Breakdown torque : 270 %
Rated speed : 1470 rpm

Moment of inertia (J) : 0.2063 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 8	
Date					
	24/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump NEMA
Premium Efficiency Three-Phase

Product code : 10781668



Performance : 415 V 50 Hz 4P IE3

Rated current : 34.3 A
LRC : 7.1
Rated torque : 12.3 kgfm
Locked rotor torque : 270 %
Breakdown torque : 300 %
Rated speed : 1475 rpm

Moment of inertia (J) : 0.2063 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 8Revision		
Checked by				
Date	24/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump NEMA
Premium Efficiency Three-Phase

Product code : 10781668



Performance : 380 V 50 Hz 4P IE2

Rated current : 42.9 A
LRC : 5.0
Rated torque : 14.9 kgfm
Locked rotor torque : 170 %
Breakdown torque : 200 %
Rated speed : 1460 rpm

Moment of inertia (J) : 0.2063 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 6 / 8	Revision
Checked by					
Date					
	24/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump NEMA
Premium Efficiency Three-Phase

Product code : 10781668



Performance : 400 V 50 Hz 4P IE2

Rated current : 41.4 A
LRC : 5.6
Rated torque : 14.9 kgfm
Locked rotor torque : 190 %
Breakdown torque : 220 %
Rated speed : 1465 rpm

Moment of inertia (J) : 0.2063 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 7 / 8	Revision
Checked by					
Date	24/10/2024				

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : Close Coupled Pump NEMA
Premium Efficiency Three-Phase

Product code : 10781668

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 4P IE3

Rated current	: 40.1 A	Moment of inertia (J)	: 0.2063 kgm ²
LRC	: 6.1	Duty cycle	: Cont.(S1)
Rated torque	: 14.8 kgfm	Insulation class	: F
Locked rotor torque	: 210 %	Service factor	: 1.15
Breakdown torque	: 240 %	Temperature rise	: 80 K
Rated speed	: 1468 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	24/10/2024		Page 8 / 8	Revision