

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :					
Product line		: Close Coupled Pump NEMA Premium Efficiency Three-Phase		Product code : 11082680	
Frame	: 254JM		Locked rotor time	: 25s (cold) 14s (hot)	
Output	: 15 HP (11 kW)		Temperature rise	: 80 K	
Poles	: 4		Duty cycle	: Cont.(S1)	
Frequency	: 60 Hz		Ambient temperature	: -20°C to +40°C	
Rated voltage	: 575 V		Altitude	: 1000 m.a.s.l.	
Rated current	: 14.9 A		Protection degree	: IP23	
L. R. Amperes	: 100 A		Cooling method	: IC01 - ODP	
LRC	: 6.7x(Code H)		Mounting	: F-1	
No load current	: 7.20 A		Rotation ¹	: Both (CW and CCW)	
Rated speed	: 1775 rpm		Noise level ²	: 59.0 dB(A)	
Slip	: 1.39 %		Starting method	: Direct On Line	
Rated torque	: 6.13 kgfm		Approx. weight ³	: 109 kg	
Locked rotor torque	: 290 %				
Breakdown torque	: 300 %				
Insulation class	: F				
Service factor	: 1.15				
Moment of inertia (J)	: 0.0878 kgm ²				
Design	: B				
Output	25%	50%	75%	100%	
Efficiency (%)	91.0	91.7	92.4	93.0	
Power Factor	0.36	0.60	0.72	0.80	
Foundation loads					
Max. traction : 235 kgf					
Max. compression : 344 kgf					
		<u>Drive end</u>	<u>Non drive end</u>		
Bearing type	:	6309 Z C3	6209 Z C3		
Sealing	:	Without Bearing Seal	Without Bearing Seal		
Lubrication interval	:	20000 h	20000 h		
Lubricant amount	:	13 g	9 g		
Lubricant type	:	Mobil Polyrex EM			
Notes:					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	14/01/2024			1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump NEMA Premium
Efficiency Three-Phase

Product code : 11082680



Performance : 575 V 60 Hz 4P

Rated current : 14.9 A
 LRC : 6.7
 Rated torque : 6.13 kgfm
 Locked rotor torque : 290 %
 Breakdown torque : 300 %
 Rated speed : 1775 rpm

Moment of inertia (J) : 0.0878 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
		Page	Revision	
		2 / 2		