

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11164525

Frame	: 404/5T	Locked rotor time	: 23s (cold) 13s (hot)
Output	: 100 HP (75 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 90.4 A	Protection degree	: IP55
L. R. Amperes	: 660 A	Cooling method	: IC411 - TEFC
LRC	: 7.3x(Code H)	Mounting	: F-1
No load current	: 30.4 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1780 rpm	Noise level ²	: 68.0 dB(A)
Slip	: 1.11 %	Vibration	: B
Rated torque	: 40 kgfm	Starting method	: Direct On Line
Locked rotor torque	: 240 %	Approx. weight ³	: 517 kg
Breakdown torque	: 260 %	Painting plan	: 203A (ISO 12944 - C3)
Insulation class	: F	Color	: RAL 5009
Service factor	: 1.25	Design	: B
Moment of inertia (J)	: 1.26 kgm ²		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	95.0	95.0	95.4	Max. traction	: 781 kgf
Power Factor	0.00	0.77	0.84	0.87	Max. compression	: 1306 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.7	3.8	3.7	2.2	1.5	0.9	0.6

	Drive end	Non drive end
Bearing type	: NU-316 C3	6314 C3
Sealing	: WSeal	WSeal
Lubrication interval	: 7000 h	12000 h
Lubricant amount	: 34 g	27 g
Lubricant type	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	04/10/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11164525



Performance : 575 V 60 Hz 4P

Rated current : 90.4 A
LRC : 7.3
Rated torque : 40 kgfm
Locked rotor torque : 240 %
Breakdown torque : 260 %
Rated speed : 1780 rpm

Moment of inertia (J) : 1.26 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2	Revision
Checked by					
Date	04/10/2026				