

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11165765

Frame	: 586/7T	Locked rotor time	: 52s (cold) 29s (hot)
Output	: 350 HP (260 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 341 A	Protection degree	: IP55
L. R. Amperes	: 2044 A	Cooling method	: IC411 - TEFC
LRC	: 6.0x(Code G)	Mounting	: F-1
No load current	: 148 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1193 rpm	Noise level ²	: 77.0 dB(A)
Slip	: 0.58 %	Vibration	: B
Rated torque	: 212 kgfm	Starting method	: Direct On Line
Locked rotor torque	: 190 %	Approx. weight ³	: 1716 kg
Breakdown torque	: 210 %	Painting plan	: 203A (ISO 12944 - C3)
Insulation class	: F	Color	: RAL 5009
Service factor	: 1.15	Design	: B
Moment of inertia (J)	: 13.8 kgm ²		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	95.2	95.8	95.8	Max. traction	: 2191 kgf
Power Factor	0.67	0.76	0.80	Max. compression	: 3930 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.9	3.6	2.8	3.2	2.1	1.7	1.0

	Drive end	Non drive end
Bearing type	: NU-322 C3	: 6319 C3
Sealing	: Taconite Labyrinth	: Taconite Labyrinth
Lubrication interval	: 7000 h	: 13000 h
Lubricant amount	: 60 g	: 45 g
Lubricant type	: Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3 Revision		
Checked by				
Date	08/10/2026			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by					
Date	08/10/2026				
				2 / 3	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165765



Performance : 575 V 60 Hz 6P

Rated current : 341 A
LRC : 6.0
Rated torque : 212 kgfm
Locked rotor torque : 190 %
Breakdown torque : 210 %
Rated speed : 1193 rpm

Moment of inertia (J) : 13.8 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 3	Revision
Checked by					
Date	08/10/2026				