

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Explosion Proof Single-Phase Product code : 11260265

Frame	: A56CEX	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 0.25 HP (0.18 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 115/208-230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 4.40/2.10-2.20 A	Protection degree	: IP44
L. R. Amperes	: 28.6/13.7-14.3 A	Cooling method	: IC411 - TEFC
LRC	: 6.5x(Code P)	Mounting	: F-1
No load current	: 3.40/1.47-1.70 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1760 rpm	Starting method	: Direct On Line
Slip	: 2.22 %	Approx. weight ³	: 14.0 kg
Rated torque	: 0 kgfm	Painting plan	: 207N (ISO 12944 - C2)
Locked rotor torque	: 300 %	Color	: RAL 7022
Breakdown torque	: 300 %		
Insulation class	: B		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0026 kgm ²		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	52.0	61.0	64.0	Max. traction	: 3 kgf
Power Factor	0.40	0.49	0.56	Max. compression	: 16 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6203 ZZ	6203 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	05/10/2026			

LOAD PERFORMANCE CURVE


Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Explosion Proof Single-Phase

Product code : 11260265



Performance : 115/208-230 V 60 Hz 4P

Rated current : 4.40/2.10-2.20 A
LRC : 6.5
Rated torque : 0 kgfm
Locked rotor torque : 300 %
Breakdown torque : 300 %
Rated speed : 1760 rpm

Moment of inertia (J) : 0.0026 kgm²
Duty cycle : Cont.(S1)
Insulation class : B
Service factor :
Temperature rise : 80 K

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2	Revision
Checked by					
Date	05/10/2026				