# DATA SHEET

## Single Phase Induction Motor - Squirrel Cage

Customer :

Product line : Explosion Proof Single-Phase  Product code : 11260295

| | | | |
|---|---|---|---|
| Frame | : B56CEX | Locked rotor time | : 10s (cold) 6s (hot) |
| Output | : 0.5 HP (0.37 kW) | Temperature rise | : 80 K |
| Poles | : 4 | Duty cycle | : Cont.(S1) |
| Frequency | : 60 Hz | Ambient temperature | : -20°C to +40°C |
| Rated voltage | : 115/208-230 V | Altitude | : 1000 m.a.s.l. |
| Rated current | : 7.40/3.60-3.70 A | Protection degree | : IP44 |
| L. R. Amperes | : 44.4/21.6-22.2 A | Cooling method | : IC411 - TEFC |
| LRC | : 6.0x(Code M) | Mounting | : F-1 |
| No load current | : 6.00/2.59-3.00 A | Rotation[1] | : Both (CW and CCW) |
| Rated speed | : 1750 rpm | Starting method | : Direct On Line |
| Slip | : 2.78 % | Approx. weight[3] | : 17.0 kg |
| Rated torque | : 0 kgfm | Painting plan | : 207N (ISO 12944 - C2) |
| Locked rotor torque | : 280 % | Color | : RAL 7022 |
| Breakdown torque | : 220 % | | |
| Insulation class | : B | | |
| Service factor | : 1.15 | | |
| Moment of inertia (J) | : 0.0041 kgm² | | |

| Output | 50% | 75% | 100% |
|---|---|---|---|
| Efficiency (%) | 57.0 | 64.0 | 68.6 |
| Power Factor | 0.44 | 0.55 | 0.63 |

Foundation loads

| | |
|---|---|
| Max. traction | : 6 kgf |
| Max. compression | : 23 kgf |

| | | Drive end | Non drive end |
|---|---|---|---|
| Bearing type | : | 6203 ZZ | 6203 ZZ |
| Sealing | : | Without Bearing Seal | Without Bearing Seal |
| Lubrication interval | : | - | - |
| Lubricant amount | : | - | - |
| Lubricant type | : | Mobil Polyrex EM | |

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |


| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 09/10/2026 | | 1 / 2 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

# LOAD PERFORMANCE CURVE

## Single Phase Induction Motor - Squirrel Cage

| | | | |
|---|---|---|---|
| Customer | : | | |
| Product line | : Explosion Proof Single-Phase | Product code : | 11260295 |




| | | | |
|---|---|---|---|
| Performance | : 115/208-230 V 60 Hz 4P | | |
| Rated current | : 7.40/3.60-3.70 A | Moment of inertia (J) | : 0.0041 kgm² |
| LRC | : 6.0 | Duty cycle | : Cont.(S1) |
| Rated torque | : 0 kgfm | Insulation class | : B |
| Locked rotor torque | : 280 % | Service factor | : |
| Breakdown torque | : 220 % | Temperature rise | : 80 K |
| Rated speed | : 1750 rpm | | |

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 09/10/2026 | | 2 / 2 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice