DATASHEET
Power Factor Correction Capacitors

Main Features

Reference	: UCWT
Product code	: 11314667
Rated operational voltage Ue	: 480V60Hz
Series	: E
Reactive power	: 7.5 kVAr
Operational frequency	: 60 Hz

Basic Data

Number of phases	: Three-phase
Series	: E
Reactive power	: 7.5 kVAr
Operational frequency	: 60 Hz
Rated operational voltage Ue	: 480V60Hz

Operating voltage	Reactive Powers	
	60 Hz	50 Hz
480	7,50	6,25
440	6,30	5,25
415	5,61	4,67

Capacitance (delta connected)	: 28.8
Capacitance tolerance	: ±5%
Rated current	: 9,02A
Lifespan	: 150.000 h
Temperature class	: -25/D
Safety system	: Self-healing polypropylene film / Over-pressure disconnection
Max. short circuit capacity	: 10 kA
Discharge resistance conection	: Fast-on
Discharge resistance	: External
Impregnation	: Polyurethane resin
Maximum dV/dt	: <30 V/µs
Maximum current (short periods of time)	: 1.5 x In
Maximum inrush current	: <100 x In
Cover type	: Aluminium
Protection degree	: IP20
Mounting position	: Vertical
Minimum free distance required - top	: 20 mm (0.79 in)
Minimum free distance required - side	: 20 mm (0.79 in)

Connection

Terminal type	: Screw
Screw type	: M4x16,5 Slot/Phillips
Cable gauge of power supply	
- IEC Standard	: 0,5 mm² / 20 AWG ... 6 mm² / 9 AWG
- UL Standard	: Not available
Tightening torque (terminals)	
- IEC Standard	: 1,5 N.m / 1.11 lbf-in ... 2,5 N.m / 22.2 lbf-in
- UL Standard	: Not available
Tightening torque for connection	
- IEC Standard	: 14 N.m / 123.9 lbf-in
- UL Standard	: Not available

Ambient conditions

Temperature	
- Operation	: -25°C / -13 °F ... 55°C / 131 °F
- Storage	: Not available
Maximum average ambient temperature 24 h	: 45°C / 113 °F
Maximum average temperature 1 year	: 35°C / 95 °F
Maximum permissible operating altitude	: 2.000 m / 6562 ft

Dimensions

Diameter	: 75mm / 2.95 in
Height	: 225 mm / 8.86 in
Gross weight	: 1,503 kg / 3.314 lb

Compliance/standards

- IEC 60831-1-2
- UL 810

Certifications

- 00022

Notes

1) Image merely illustrative;