

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :					
Product line		: Saw Arbor Motor Standard Efficiency Three-Phase		Product code : 11451064	
Frame	: 90L/MS	Locked rotor time	: 12s (cold) 7s (hot)		
Output	: 10 HP (7.5 kW)	Temperature rise	: 80 K		
Poles	: 2	Duty cycle	: S1		
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C		
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.		
Rated current	: 27.2-24.6/12.3 A	Protection degree	: IP54		
L. R. Amperes	: 236-214/107 A	Cooling method	: IC411 - TEFC		
LRC	: 8.7	Mounting	: B3R(D)		
No load current	: 9.94-8.99/4.50 A	Rotation ¹	: CW		
Rated speed	: 3480 rpm	Noise level ²	: 68.0 dB(A)		
Slip	: 3.33 %	Starting method	: Direct On Line		
Rated torque	: 2.09 kgfm	Approx. weight ³	: 76.1 kg		
Locked rotor torque	: 400 %				
Breakdown torque	: 420 %				
Insulation class	: F				
Service factor	: 1.00				
Moment of inertia (J)	: 0.0140 kgm ²				
Design	: N				
Output	50%	75%	100%	Foundation loads	
Efficiency (%)	82.0	84.5	85.0	Max. traction : 180 kgf	
Power Factor	0.77	0.86	0.90	Max. compression : 257 kgf	
		<u>Drive end</u>	<u>Non drive end</u>		
Bearing type	:	6308 ZZ	6208 ZZ		
Sealing	:	Without Bearing Seal	Without Bearing Seal		
Lubrication interval	:	-	-		
Lubricant amount	:	-	-		
Lubricant type	:	Mobil Polyrex EM			
Notes:					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	14/01/2024			1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Saw Arbor Motor Standard Efficiency Three-Phase Product code : 11451064

LOAD PERFORMANCE CURVE



Performance : 208-230/460 V 60 Hz 2P

Rated current : 27.2-24.6/12.3 A
 LRC : 8.7
 Rated torque : 2.09 kgfm
 Locked rotor torque : 400 %
 Breakdown torque : 420 %
 Rated speed : 3480 rpm

Moment of inertia (J) : 0.0140 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	14/01/2024			