

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : ODP NEMA Premium Efficiency Three-Phase Product code : 11527210

Frame	: 326T	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 30 HP (22 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 28.8 A	Protection degree	: IP23
L. R. Amperes	: 179 A	Cooling method	: IC01 - ODP
LRC	: 6.2x(Code G)	Mounting	: F-1
No load current	: 12.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1180 rpm	Noise level ²	: 60.0 dB(A)
Slip	: 1.67 %	Starting method	: Direct On Line
Rated torque	: 18.5 kgfm	Approx. weight ³	: 249 kg
Locked rotor torque	: 220 %		
Breakdown torque	: 270 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.4126 kgm ²		
Design	: B		

Output	50%	75%	100%	Foundation loads
Efficiency (%)	91.7	93.0	93.6	Max. traction
Power Factor	0.65	0.77	0.82	Max. compression
				: 503 kgf
				: 752 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6312 Z C3	6212 Z C3
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	21 g	13 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 1 / 2	Revision
Checked by					
Date	05/02/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : ODP NEMA Premium Efficiency Three-Phase

Product code : 11527210



Performance : 575 V 60 Hz 6P

Rated current : 28.8 A
 LRC : 6.2
 Rated torque : 18.5 kgfm
 Locked rotor torque : 220 %
 Breakdown torque : 270 %
 Rated speed : 1180 rpm

Moment of inertia (J) : 0.4126 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	05/02/2024			