

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :							
Product line	: W22 NEMA Premium Efficiency Three-Phase	Product code :	11535564				
Frame	: 364/5TC	Cooling method	: IC411 - TEFC				
Insulation class	: F	Mounting	: F-1				
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)				
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line				
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 415 kg				
Protection degree	: IP55	Moment of inertia (J)	: 1.36 kgm ²				
Design	: B						
Output [HP]	50	40	40	40	50	50	50
Poles	6	6	6	6	6	6	6
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	115/57.4	57.7	55.5	53.5	71.3	67.2	65.5
L. R. Amperes [A]	735/367	358	377	396	349	370	400
LRC [A]	6.4x(Code G)	6.2x(Code G)	6.8x(Code H)	7.4x(Code J)	4.9x(Code E)	5.5x(Code F)	6.1x(Code G)
No load current [A]	40.0/20.0	20.0	21.5	22.5	20.5	21.5	22.5
Rated speed [RPM]	1183	983	985	985	975	979	980
Slip [%]	1.42	1.70	1.50	1.50	2.50	2.10	2.00
Rated torque [kgfm]	30.7	29.5	29.5	29.5	37.2	37.1	37.0
Locked rotor torque [%]	200	200	229	250	160	180	200
Breakdown torque [%]	240	240	260	290	190	210	229
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	80 K	80 K
Locked rotor time	32s (cold) 18s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)
Noise level ²	66.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)
Efficiency (%)	25%						
	50%	93.6	92.7	92.7	92.6	93.0	93.0
	75%	94.1	92.8	93.1	93.1	92.4	93.0
	100%	94.1	92.9	92.9	92.9	91.7	92.4
Power Factor	25%						
	50%	0.74	0.72	0.70	0.66	0.77	0.75
	75%	0.83	0.82	0.80	0.79	0.84	0.83
	100%	0.86	0.85	0.84	0.84	0.86	0.86
Losses at normative operating points (speed;torque), in percentage of rated output power							
Losses (%)	P1 (0,9;1,0)	6.2	6.2	6.2	6.2	6.2	6.2
	P2 (0,5;1,0)	5.2	5.2	5.2	5.2	5.2	5.2
	P3 (0,25;1,0)	4.6	4.6	4.6	4.6	4.6	4.6
	P4 (0,9;0,5)	2.8	2.8	2.8	2.8	2.8	2.8
	P5 (0,5;0,5)	1.9	1.9	1.9	1.9	1.9	1.9
	P6 (0,5;0,25)	1.2	1.2	1.2	1.2	1.2	1.2
	P7 (0,25;0,25)	0.8	0.8	0.8	0.8	0.8	0.8
Bearing type	: Drive end 6314 C3	Non drive end 6314 C3	Foundation loads				
Sealing	: Oil Seal	Oil Seal	Max. traction : 749 kgf				
Lubrication interval	: 17000 h	17000 h	Max. compression : 1164 kgf				
Lubricant amount	: 27 g	27 g					
Lubricant type	: Mobil Polyrex EM						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date	
Performed by							
Checked by					Page	Revision	
Date	18/03/2024				1 / 9		

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 127A SF 1.10 SFA 140A

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	18/03/2024		2 / 9	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 11535564



Performance : 230/460 V 60 Hz 6P

Rated current : 115/57.4 A
 LRC : 6.4
 Rated torque : 30.7 kgfm
 Locked rotor torque : 200 %
 Breakdown torque : 240 %
 Rated speed : 1183 rpm

Moment of inertia (J) : 1.36 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 11535564



Performance : 380 V 50 Hz 6P IE3

Rated current : 57.7 A
 LRC : 6.2
 Rated torque : 29.5 kgfm
 Locked rotor torque : 200 %
 Breakdown torque : 240 %
 Rated speed : 983 rpm

Moment of inertia (J) : 1.36 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 11535564



Performance : 400 V 50 Hz 6P IE3

Rated current : 55.5 A
 LRC : 6.8
 Rated torque : 29.5 kgfm
 Locked rotor torque : 229 %
 Breakdown torque : 260 %
 Rated speed : 985 rpm

Moment of inertia (J) : 1.36 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		5 / 9		
Date		18/03/2024		

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 11535564



Performance : 415 V 50 Hz 6P IE3

Rated current : 53.5 A
 LRC : 7.4
 Rated torque : 29.5 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 290 %
 Rated speed : 985 rpm

Moment of inertia (J) : 1.36 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 6 / 9	Revision
Checked by				
Date	18/03/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 11535564



Performance : 380 V 50 Hz 6P IE1

Rated current : 71.3 A
 LRC : 4.9
 Rated torque : 37.2 kgfm
 Locked rotor torque : 160 %
 Breakdown torque : 190 %
 Rated speed : 975 rpm

Moment of inertia (J) : 1.36 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 105 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 11535564



Performance : 400 V 50 Hz 6P IE2

Rated current	: 67.2 A	Moment of inertia (J)	: 1.36 kgm ²
LRC	: 5.5	Duty cycle	: Cont.(S1)
Rated torque	: 37.1 kgfm	Insulation class	: F
Locked rotor torque	: 180 %	Service factor	: 1.00
Breakdown torque	: 210 %	Temperature rise	: 80 K
Rated speed	: 979 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 8 / 9	Revision
Checked by				
Date	18/03/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 11535564



Performance : 415 V 50 Hz 6P IE2

Rated current : 65.5 A
 LRC : 6.1
 Rated torque : 37.0 kgfm
 Locked rotor torque : 200 %
 Breakdown torque : 229 %
 Rated speed : 980 rpm

Moment of inertia (J) : 1.36 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date	
Performed by					
Checked by					
Date					18/03/2024
		Page	Revision		
		9 / 9			