

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 Tru-Metric IE3 Three-Phase Product code : 11706548

Frame	: 132S	Locked rotor time	: 27s (cold) 15s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 18.1/9.07 A	Protection degree	: IP55
L. R. Amperes	: 174/87.1 A	Cooling method	: IC411 - TEFC
LRC	: 9.6	Mounting	: B3L(E)
No load current	: 8.00/4.00 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3555 rpm	Noise level ²	: 68.0 dB(A)
Slip	: 1.25 %	Starting method	: Direct On Line
Rated torque	: 1.53 kgfm	Approx. weight ³	: 63.6 kg
Locked rotor torque	: 290 %		
Breakdown torque	: 409 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0216 kgm ²		
Design	: N		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	86.5	89.0	89.5	Max. traction	: 84 kgf
Power Factor	0.69	0.80	0.85	Max. compression	: 148 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.0	7.9	6.8	7.0	4.0	3.2	1.9

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6308 ZZ	6207 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		1 / 2		
Date	14/01/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 Tru-Metric IE3 Three-Phase

Product code : 11706548



Performance : 230/460 V 60 Hz 2P

Rated current : 18.1/9.07 A
 LRC : 9.6
 Rated torque : 1.53 kgfm
 Locked rotor torque : 290 %
 Breakdown torque : 409 %
 Rated speed : 3555 rpm

Moment of inertia (J) : 0.0216 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				
			2 / 2	