

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 Tru-Metric IE3 Three-Phase Product code : 11706637

Frame	: 160L	Locked rotor time	: 14s (cold) 8s (hot)
Output	: 25 HP (18.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 59.8/29.9 A	Protection degree	: IP55
L. R. Amperes	: 568/284 A	Cooling method	: IC411 - TEFC
LRC	: 9.5	Mounting	: B3L(E)
No load current	: 24.0/12.0 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 3555 rpm	Noise level <sup>2</sup>	: 72.0 dB(A)
Slip	: 1.25 %	Starting method	: Direct On Line
Rated torque	: 5.10 kgfm	Approx. weight <sup>3</sup>	: 156 kg
Locked rotor torque	: 370 %		
Breakdown torque	: 430 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0555 kgm <sup>2</sup>		
Design	: N		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	90.6	92.2	92.4	Max. traction	: 267 kgf
Power Factor	0.67	0.79	0.84	Max. compression	: 423 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
7.8	6.0	5.5	4.6	2.8	2.1	1.3

	Drive end	Non drive end
Bearing type	: 6309 C3	6209 C3
Sealing	: V'Ring	V'Ring
Lubrication interval	: 19000 h	20000 h
Lubricant amount	: 13 g	9 g
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	14/01/2024		1 / 2	

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 Tru-Metric IE3 Three-Phase

Product code : 11706637



Performance : 230/460 V 60 Hz 2P

Rated current : 59.8/29.9 A  
 LRC : 9.5  
 Rated torque : 5.10 kgfm  
 Locked rotor torque : 370 %  
 Breakdown torque : 430 %  
 Rated speed : 3555 rpm

Moment of inertia (J) : 0.0555 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.25  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		2 / 2		
Date		14/01/2024		