

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line		: W22 NEMA Premium Efficiency Three-Phase		Product code :		11716179
Frame	:	364/5TC		Locked rotor time	:	27s (cold) 15s (hot)
Output	:	60 HP (45 kW)		Temperature rise	:	80 K
Poles	:	4		Duty cycle	:	Cont.(S1)
Frequency	:	60 Hz		Ambient temperature	:	-20°C to +40°C
Rated voltage	:	575 V		Altitude	:	1000 m.a.s.l.
Rated current	:	57.3 A		Protection degree	:	IP55
L. R. Amperes	:	355 A		Cooling method	:	IC411 - TEFC
LRC	:	6.2x(Code G)		Mounting	:	F-1
No load current	:	22.4 A		Rotation ¹	:	Both (CW and CCW)
Rated speed	:	1780 rpm		Noise level ²	:	67.0 dB(A)
Slip	:	1.11 %		Starting method	:	Direct On Line
Rated torque	:	24.5 kgfm		Approx. weight ³	:	399 kg
Locked rotor torque	:	220 %				
Breakdown torque	:	240 %				
Insulation class	:	F				
Service factor	:	1.25				
Moment of inertia (J)	:	0.9448 kgm ²				
Design	:	B				
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	94.1	94.5	95.0	Max. traction	:	460 kgf
Power Factor	0.71	0.80	0.83	Max. compression	:	859 kgf
Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
5.1	4.1	3.8	2.6	1.7	1.2	0.8
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	6314 C3		6314 C3		
Sealing	:	Oil Seal		Oil Seal		
Lubrication interval	:	12000 h		12000 h		
Lubricant amount	:	27 g		27 g		
Lubricant type	:	Mobil Polyrex EM				
Notes						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	17/07/2024				1 / 2	


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11716179



Performance : 575 V 60 Hz 4P

Rated current	: 57.3 A	Moment of inertia (J)	: 0.9448 kgm ²
LRC	: 6.2	Duty cycle	: Cont.(S1)
Rated torque	: 24.5 kgfm	Insulation class	: F
Locked rotor torque	: 220 %	Service factor	: 1.25
Breakdown torque	: 240 %	Temperature rise	: 80 K
Rated speed	: 1780 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	17/07/2024			