

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase      Product code : 11941785

Frame	: 324/6T	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation <sup>1</sup>	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight <sup>2</sup>	: 0.0 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.5023 kgm <sup>2</sup>
Design	: B		

Output [HP]	25	20	20	20	25	25	25
Poles	8	8	8	8	8	8	8
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	460	380	400	415	380	400	415
Rated current [A]	35.9	35.3	35.6	36.4	42.3	41.4	41.1
L. R. Amperes [A]	187	177	192	200	178	190	197
LRC [A]	5.2x(Code G)	5.0x(Code G)	5.4x(Code H)	5.5x(Code J)	4.2x(Code E)	4.6x(Code F)	4.8x(Code G)
No load current [A]	20.0	19.6	22.2	24.6	19.6	22.2	24.6
Rated speed [RPM]	880	730	730	735	725	725	730
Slip [%]	2.22	2.67	2.67	2.00	3.33	3.33	2.67
Rated torque [kgfm]	20.6	19.9	19.9	19.7	25.0	25.0	24.9
Locked rotor torque [%]	200	190	210	240	150	170	190
Breakdown torque [%]	229	229	250	280	180	200	220
Service factor	1.25	1.15	1.15	1.15	1.15	1.15	1.15
Temperature rise	80 K	80 K	80 K	80 K	105 K	80 K	80 K
Locked rotor time	41s (cold) 23s (hot)	30s (cold) 17s (hot)	30s (cold) 17s (hot)	30s (cold) 17s (hot)	30s (cold) 17s (hot)	30s (cold) 17s (hot)	30s (cold) 17s (hot)
Noise level <sup>2</sup>	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)
Efficiency (%)	25%						
	50%	89.5	89.3	87.2	86.2	89.5	88.5
	75%	91.0	90.1	89.1	88.6	90.2	89.5
	100%	91.0	89.6	89.6	89.6	88.5	89.5
Power Factor	25%						
	50%	0.51	0.51	0.46	0.42	0.58	0.53
	75%	0.64	0.64	0.59	0.55	0.70	0.66
	100%	0.71	0.71	0.67	0.64	0.75	0.72

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	9.5	9.5	9.5	9.5	9.5	9.5
	P2 (0,5;1,0)	7.4	7.4	7.4	7.4	7.4	7.4
	P3 (0,25;1,0)	6.5	6.5	6.5	6.5	6.5	6.5
	P4 (0,9;0,5)	5.8	5.8	5.8	5.8	5.8	5.8
	P5 (0,5;0,5)	3.9	3.9	3.9	3.9	3.9	3.9
	P6 (0,5;0,25)	3.1	3.1	3.1	3.1	3.1	3.1
	P7 (0,25;0,25)	2.2	2.2	2.2	2.2	2.2	2.2

Bearing type	: Drive end 6312 C3      Non drive end 6212 C3	Foundation loads Max. traction : 688 kgf Max. compression : 688 kgf
Sealing	: Taconite Labyrinth      Taconite Labyrinth	
Lubrication interval	: 20000 h      20000 h	
Lubricant amount	: 21 g      13 g	
Lubricant type	: Mobil Polyrex EM	

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/01/2024		1 / 9	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/01/2024		2 / 9	

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 IEEE 841 NEMA Premium Efficiency  
Three-Phase

Product code : 11941785



Performance : 460 V 60 Hz 8P

Rated current : 35.9 A  
 LRC : 5.2  
 Rated torque : 20.6 kgfm  
 Locked rotor torque : 200 %  
 Breakdown torque : 229 %  
 Rated speed : 880 rpm

Moment of inertia (J) : 0.5023 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.25  
 Temperature rise : 80 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
			Page	Revision
			3 / 9	

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase      Product code : 11941785

LOAD PERFORMANCE CURVE



Performance : 380 V 50 Hz 8P IE3

Rated current	: 35.3 A	Moment of inertia (J)	: 0.5023 kgm <sup>2</sup>
LRC	: 5.0	Duty cycle	: Cont.(S1)
Rated torque	: 19.9 kgfm	Insulation class	: F
Locked rotor torque	: 190 %	Service factor	: 1.15
Breakdown torque	: 229 %	Temperature rise	: 80 K
Rated speed	: 730 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 9	Revision
Checked by				
Date	13/01/2024			

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 IEEE 841 NEMA Premium Efficiency  
Three-Phase

Product code : 11941785



Performance : 400 V 50 Hz 8P IE3

Rated current : 35.6 A  
 LRC : 5.4  
 Rated torque : 19.9 kgfm  
 Locked rotor torque : 210 %  
 Breakdown torque : 250 %  
 Rated speed : 730 rpm

Moment of inertia (J) : 0.5023 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.15  
 Temperature rise : 80 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 5 / 9	Revision
Checked by				
Date	13/01/2024			

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase      Product code : 11941785

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 8P IE3

Rated current	: 36.4 A	Moment of inertia (J)	: 0.5023 kgm <sup>2</sup>
LRC	: 5.5	Duty cycle	: Cont.(S1)
Rated torque	: 19.7 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.15
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 735 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by			6 / 9	
Date	13/01/2024			

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase

Product code : 11941785



Performance : 380 V 50 Hz 8P IE1

Rated current : 42.3 A  
 LRC : 4.2  
 Rated torque : 25.0 kgfm  
 Locked rotor torque : 150 %  
 Breakdown torque : 180 %  
 Rated speed : 725 rpm

Moment of inertia (J) : 0.5023 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.15  
 Temperature rise : 105 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase      Product code : 11941785

LOAD PERFORMANCE CURVE



Performance : 400 V 50 Hz 8P IE2

Rated current	: 41.4 A	Moment of inertia (J)	: 0.5023 kgm <sup>2</sup>
LRC	: 4.6	Duty cycle	: Cont.(S1)
Rated torque	: 25.0 kgfm	Insulation class	: F
Locked rotor torque	: 170 %	Service factor	: 1.15
Breakdown torque	: 200 %	Temperature rise	: 80 K
Rated speed	: 725 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 8 / 9	Revision
Checked by				
Date	13/01/2024			



# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase

Product code : 11941785



Performance : 415 V 50 Hz 8P IE2

Rated current : 41.1 A  
 LRC : 4.8  
 Rated torque : 24.9 kgfm  
 Locked rotor torque : 190 %  
 Breakdown torque : 220 %  
 Rated speed : 730 rpm

Moment of inertia (J) : 0.5023 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.15  
 Temperature rise : 80 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		9 / 9		
Date		13/01/2024		