

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer : \_\_\_\_\_

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase      Product code : 11943600

Frame	: 444/5T	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation <sup>1</sup>	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight <sup>2</sup>	: 0.0 kg
Protection degree	: IP55	Moment of inertia (J)	: 3.68 kgm <sup>2</sup>
Design	: B		

Output [HP]	100	75	75	75	100	100	100
Poles	6	6	6	6	6	6	6
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	460	380	400	415	380	400	415
Rated current [A]	121	107	104	102	145	139	135
L. R. Amperes [A]	714	674	718	755	682	723	770
LRC [A]	5.9x(Code G)	6.3x(Code G)	6.9x(Code H)	7.4x(Code J)	4.7x(Code E)	5.2x(Code F)	5.7x(Code G)
No load current [A]	42.0	41.4	44.9	47.7	41.4	44.9	47.7
Rated speed [RPM]	1185	985	990	990	980	985	985
Slip [%]	1.25	1.50	1.00	1.00	2.00	1.50	1.50
Rated torque [kgfm]	61.0	54.9	54.9	54.8	73.7	73.5	73.5
Locked rotor torque [%]	220	229	250	270	170	190	200
Breakdown torque [%]	229	250	280	310	180	200	220
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	36s (cold) 20s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)
Noise level <sup>2</sup>	69.0 dB(A)	65.0 dB(A)	65.0 dB(A)	65.0 dB(A)	65.0 dB(A)	65.0 dB(A)	65.0 dB(A)
Efficiency (%)	25%						
	50%	94.5	93.8	93.8	93.7	94.5	94.5
	75%	95.0	94.3	94.6	94.6	94.0	94.5
	100%	95.0	94.2	94.5	94.6	93.6	94.0
Power Factor	25%						
	50%	0.68	0.64	0.60	0.57	0.74	0.71
	75%	0.78	0.77	0.74	0.71	0.82	0.80
	100%	0.82	0.83	0.81	0.79	0.84	0.83

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	5.7	6.7	6.3	6.2	7.4	6.9	6.9
	P2 (0,5;1,0)	4.4	5.3	5.0	4.9	6.1	5.6	5.6
	P3 (0,25;1,0)	3.9	4.8	4.5	4.4	5.5	5.1	5.1
	P4 (0,9;0,5)	3.2	3.7	3.5	3.4	4.0	3.8	3.8
	P5 (0,5;0,5)	2.1	2.4	2.3	2.3	2.7	2.5	2.5
	P6 (0,5;0,25)	1.6	1.8	1.7	1.7	2.0	1.9	1.9
	P7 (0,25;0,25)	1.0	1.2	1.1	1.1	1.3	1.2	1.2

Bearing type	: Drive end 6319 C3      Non drive end 6316 C3	Foundation loads Max. traction : 1418 kgf Max. compression : 1418 kgf
Sealing	: Taconite Labyrinth      Taconite Labyrinth	
Lubrication interval	: 13000 h      16000 h	
Lubricant amount	: 45 g      34 g	
Lubricant type	: Mobil Polyrex EM	

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/01/2024		1 / 9	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/01/2024		2 / 9	



# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase      Product code : 11943600

LOAD PERFORMANCE CURVE



Performance : 380 V 50 Hz 6P IE3

Rated current	: 107 A	Moment of inertia (J)	: 3.68 kgm <sup>2</sup>
LRC	: 6.3	Duty cycle	: Cont.(S1)
Rated torque	: 54.9 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.00
Breakdown torque	: 250 %	Temperature rise	: 80 K
Rated speed	: 985 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 9	Revision
Checked by				
Date	13/01/2024			


# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase      Product code : 11943600



Performance : 400 V 50 Hz 6P IE3

Rated current	: 104 A	Moment of inertia (J)	: 3.68 kgm <sup>2</sup>
LRC	: 6.9	Duty cycle	: Cont.(S1)
Rated torque	: 54.9 kgfm	Insulation class	: F
Locked rotor torque	: 250 %	Service factor	: 1.00
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 990 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 5 / 9	Revision
Checked by				
Date	13/01/2024			


# LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase      Product code : 11943600



Performance : 415 V 50 Hz 6P IE3

Rated current	: 102 A	Moment of inertia (J)	: 3.68 kgm <sup>2</sup>
LRC	: 7.4	Duty cycle	: Cont.(S1)
Rated torque	: 54.8 kgfm	Insulation class	: F
Locked rotor torque	: 270 %	Service factor	: 1.00
Breakdown torque	: 310 %	Temperature rise	: 80 K
Rated speed	: 990 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 6 / 9	Revision
Checked by				
Date	13/01/2024			

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase

Product code : 11943600



Performance : 380 V 50 Hz 6P IE1

Rated current : 145 A  
 LRC : 4.7  
 Rated torque : 73.7 kgfm  
 Locked rotor torque : 170 %  
 Breakdown torque : 180 %  
 Rated speed : 980 rpm

Moment of inertia (J) : 3.68 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 105 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date	
Performed by					
Checked by					
Date					13/01/2024
		Page	Revision		
		7 / 9			

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase      Product code : 11943600

LOAD PERFORMANCE CURVE



Performance : 400 V 50 Hz 6P IE2

Rated current	: 139 A	Moment of inertia (J)	: 3.68 kgm <sup>2</sup>
LRC	: 5.2	Duty cycle	: Cont.(S1)
Rated torque	: 73.5 kgfm	Insulation class	: F
Locked rotor torque	: 190 %	Service factor	: 1.00
Breakdown torque	: 200 %	Temperature rise	: 105 K
Rated speed	: 985 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 8 / 9	Revision
Checked by				
Date	13/01/2024			



