

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W21 Explosion Proof NEMA Premium Efficiency Three-Phase Product code : 11950079

Frame	: 504/5T	Locked rotor time	: 52s (cold) 29s (hot)
Output	: 200 HP (150 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 184 A	Protection degree	: IP55
L. R. Amperes	: 1251 A	Cooling method	: IC411 - TEFC
LRC	: 6.8x(Code G)	Mounting	: F-1
No load current	: 59.2 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1782 rpm	Noise level ²	: 82.0 dB(A)
Slip	: 1.00 %	Starting method	: Direct On Line
Rated torque	: 81.5 kgfm	Approx. weight ³	: 1194 kg
Locked rotor torque	: 210 %		
Breakdown torque	: 229 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 3.21 kgm ²		
Design	: A		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	95.8	96.2	96.2	Max. traction	: 878 kgf
Power Factor	0.72	0.80	0.85	Max. compression	: 2072 kgf

	<u>Drive end</u>	<u>Non drive end</u>
Bearing type	: NU-319 C3	6316 C3
Sealing	: Viton Oil Seal	Viton Seal
Lubrication interval	: 4706 h	8569 h
Lubricant amount	: 45 g	34 g
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	13/01/2024	Page 1 / 3		Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/01/2024		2 / 3	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 11950079



Performance : 575 V 60 Hz 4P

Rated current : 184 A
 LRC : 6.8
 Rated torque : 81.5 kgfm
 Locked rotor torque : 210 %
 Breakdown torque : 229 %
 Rated speed : 1782 rpm

Moment of inertia (J) : 3.21 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : A

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				