

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :					
Product line		: ODP NEMA Premium Efficiency Three-Phase		Product code : 11983384	
Frame	: 284TC	Locked rotor time	: 27s (cold) 15s (hot)		
Output	: 25 HP (18.5 kW)	Temperature rise	: 80 K		
Poles	: 4	Duty cycle	: Cont.(S1)		
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C		
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.		
Rated current	: 23.9 A	Protection degree	: IP23		
L. R. Amperes	: 160 A	Cooling method	: IC01 - ODP		
LRC	: 6.7x(Code H)	Mounting	: F-1		
No load current	: 9.60 A	Rotation ¹	: Both (CW and CCW)		
Rated speed	: 1770 rpm	Noise level ²	: 62.0 dB(A)		
Slip	: 1.67 %	Starting method	: Direct On Line		
Rated torque	: 10.3 kgfm	Approx. weight ³	: 165 kg		
Locked rotor torque	: 250 %				
Breakdown torque	: 280 %				
Insulation class	: F				
Service factor	: 1.15				
Moment of inertia (J)	: 0.1435 kgm ²				
Design	: B				
Output	50%	75%	100%	Foundation loads	
Efficiency (%)	92.4	93.0	93.6	Max. traction : 328 kgf	
Power Factor	0.67	0.78	0.83	Max. compression : 493 kgf	
		<u>Drive end</u>		<u>Non drive end</u>	
Bearing type	:	6311 Z C3		6211 Z C3	
Sealing	:	Without Bearing Seal		Without Bearing Seal	
Lubrication interval	:	20000 h		20000 h	
Lubricant amount	:	18 g		11 g	
Lubricant type	:	Mobil Polyrex EM			
Notes					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	13/11/2025			1 / 2	


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : ODP NEMA Premium Efficiency Three-Phase Product code : 11983384



Performance : 575 V 60 Hz 4P

Rated current	: 23.9 A	Moment of inertia (J)	: 0.1435 kgm ²
LRC	: 6.7	Duty cycle	: Cont.(S1)
Rated torque	: 10.3 kgfm	Insulation class	: F
Locked rotor torque	: 250 %	Service factor	: 1.15
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 1770 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	13/11/2025			