

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : General High Efficiency Three-Phase Product code : 11993756

Frame	: E143/5TC	Locked rotor time	: 27s (cold) 15s (hot)
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K
Frequency	: 60 Hz	Duty cycle	: Cont.(S1)
Rated voltage	: 575 V	Ambient temperature	: -20°C to +40°C
Poles	: 4	Altitude	: 1000 m.a.s.l.
Rated current	: 1.20 A	Protection degree	: IP21
	: 7.8x(Code L)	Cooling method	: IC01 - ODP
Rated speed	: 1740 rpm	Mounting	: F-1
Rated torque	: 0.417 kgfm	Rotation ¹	: Both (CW and CCW)
Insulation class	: F	Noise level ²	: 50.0 dB(A)
Service factor	: 1.15	Starting method	: Direct On Line
Moment of inertia (J)	: 0.0053 kgm ²	Approx. weight ³	: 20.9 kg
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	80.0	81.5	82.5	Max. traction	: 31 kgf
Power Factor	0.57	0.68	0.76	Max. compression	: 52 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6205 ZZ	6204 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	22/03/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : General High Efficiency Three-Phase Product code : 11993756

LOAD PERFORMANCE CURVE



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	22/03/2026				
			Page 2 / 2	Revision	