

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 Close Coupled Pump JM NEMA Premium Efficiency Three-Phase Product code : 12037974

Frame	: 182JM	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ²	: 41.7 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.0080 kgm ²
Design	: B		

Output [HP]	3	2	2	2	3	3	3
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	7.26/3.63	3.09	3.00	2.96	4.34	4.17	4.07
L. R. Amperes [A]	62.4/31.2	29.7	32.1	32.9	29.5	31.7	33.0
LRC [A]	8.6x(Code K)	9.6x(Code L)	10.7x(Code M)	11.1x(Code N)	6.8x(Code H)	7.6x(Code J)	8.1x(Code J)
No load current [A]	2.60/1.30	1.25	1.35	1.40	1.25	1.35	1.40
Rated speed [RPM]	3510	2930	2935	2940	2880	2890	2900
Slip [%]	2.50	2.33	2.17	2.00	4.00	3.67	3.33
Rated torque [kgfm]	0.620	0.495	0.495	0.494	0.756	0.753	0.751
Locked rotor torque [%]	250	300	340	370	210	240	260
Breakdown torque [%]	380	430	480	520	290	320	350
Service factor	1.25	1.25	1.25	1.25	1.25	1.25	1.25
Temperature rise	80 K	80 K	80 K	80 K	80 K	80 K	80 K
Locked rotor time	73s (cold) 41s (hot)	54s (cold) 30s (hot)	54s (cold) 30s (hot)	54s (cold) 30s (hot)	54s (cold) 30s (hot)	54s (cold) 30s (hot)	54s (cold) 30s (hot)
Noise level ²	66.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)
Efficiency (%)	25%						
	50%	82.5	81.0	80.6	79.7	84.0	84.0
	75%	86.5	84.5	84.5	84.1	86.5	86.5
	100%	86.5	85.8	85.8	85.9	85.5	85.5
Power Factor	25%						
	50%	0.75	0.68	0.65	0.63	0.80	0.77
	75%	0.84	0.79	0.77	0.75	0.87	0.86
	100%	0.88	0.86	0.84	0.82	0.90	0.89

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	14.1	14.1	14.1	14.1	14.1	14.1	14.1
	P2 (0,5;1,0)	9.5	9.5	9.5	9.5	9.5	9.5	9.5
	P3 (0,25;1,0)	8.5	8.5	8.5	8.5	8.5	8.5	8.5
	P4 (0,9;0,5)	8.7	8.7	8.7	8.7	8.7	8.7	8.7
	P5 (0,5;0,5)	4.4	4.4	4.4	4.4	4.4	4.4	4.4
	P6 (0,5;0,25)	3.3	3.3	3.3	3.3	3.3	3.3	3.3
	P7 (0,25;0,25)	1.7	1.7	1.7	1.7	1.7	1.7	1.7

Bearing type	: Drive end	6307 ZZ	Non drive end	6206 ZZ	Foundation loads	Max. traction	: 34 kgf
	: Sealing	V'Ring	: V'Ring			Max. compression	: 76 kgf
	: Lubrication interval	-	: -				
	: Lubricant amount	-	: -				
	: Lubricant type	Mobil Polyrex EM					

This revision replaces and cancel the previous one, which must be eliminated.

(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	13/01/2024				1 / 9	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 8.01A SF 1.15 SFA 9.21A

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/01/2024		2 / 9	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM NEMA
Premium Efficiency Three-Phase

Product code : 12037974



Performance : 230/460 V 60 Hz 2P

Rated current : 7.26/3.63 A
 LRC : 8.6
 Rated torque : 0.620 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 380 %
 Rated speed : 3510 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer : _____

Product line : W22 Close Coupled Pump JM NEMA
Premium Efficiency Three-Phase

Product code : 12037974

LOAD PERFORMANCE CURVE



Performance : 380 V 50 Hz 2P IE3

Rated current : 3.09 A
LRC : 9.6
Rated torque : 0.495 kgfm
Locked rotor torque : 300 %
Breakdown torque : 430 %
Rated speed : 2930 rpm

Moment of inertia (J) : 0.0080 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 9	Revision
Checked by				
Date	13/01/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM NEMA
Premium Efficiency Three-Phase

Product code : 12037974



Performance : 400 V 50 Hz 2P IE3

Rated current : 3.00 A
 LRC : 10.7
 Rated torque : 0.495 kgfm
 Locked rotor torque : 340 %
 Breakdown torque : 480 %
 Rated speed : 2935 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer : _____

Product line : W22 Close Coupled Pump JM NEMA
Premium Efficiency Three-Phase

Product code : 12037974

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 2P IE3

Rated current : 2.96 A
LRC : 11.1
Rated torque : 0.494 kgfm
Locked rotor torque : 370 %
Breakdown torque : 520 %
Rated speed : 2940 rpm

Moment of inertia (J) : 0.0080 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 6 / 9	Revision
Checked by				
Date	13/01/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM NEMA
Premium Efficiency Three-Phase

Product code : 12037974



Performance : 380 V 50 Hz 2P IE2

Rated current : 4.34 A
LRC : 6.8
Rated torque : 0.756 kgfm
Locked rotor torque : 210 %
Breakdown torque : 290 %
Rated speed : 2880 rpm

Moment of inertia (J) : 0.0080 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 7 / 9	Revision
Checked by				
Date	13/01/2024			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 Close Coupled Pump JM NEMA
Premium Efficiency Three-Phase

Product code : 12037974

LOAD PERFORMANCE CURVE



Performance : 400 V 50 Hz 2P IE2

Rated current : 4.17 A
LRC : 7.6
Rated torque : 0.753 kgfm
Locked rotor torque : 240 %
Breakdown torque : 320 %
Rated speed : 2890 rpm

Moment of inertia (J) : 0.0080 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date	13/01/2024			
			8 / 9	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 Close Coupled Pump JM NEMA
Premium Efficiency Three-Phase

Product code : 12037974



Performance : 415 V 50 Hz 2P IE2

Rated current : 4.07 A
 LRC : 8.1
 Rated torque : 0.751 kgfm
 Locked rotor torque : 260 %
 Breakdown torque : 350 %
 Rated speed : 2900 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				