

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : ODP NEMA Premium Efficiency Three-Phase      Product code : 12101776

Frame	: 404/5TS	Locked rotor time	: 18s (cold) 10s (hot)
Output	: 150 HP (110 kW)	Temperature rise	: 105 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 130 A	Protection degree	: IP23
L. R. Amperes	: 855 A	Cooling method	: IC01 - ODP
LRC	: 6.6x(Code G)	Mounting	: F-1
No load current	: 25.6 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 3555 rpm	Noise level <sup>2</sup>	: 84.0 dB(A)
Slip	: 1.25 %	Starting method	: Direct On Line
Rated torque	: 30.6 kgfm	Approx. weight <sup>3</sup>	: 460 kg
Locked rotor torque	: 190 %		
Breakdown torque	: 250 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.5023 kgm <sup>2</sup>		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	94.5	94.5	94.5	Max. traction	: 523 kgf
Power Factor	0.86	0.89	0.90	Max. compression	: 983 kgf

	<u>Drive end</u>	<u>Non drive end</u>
Bearing type	: 6314 C3	6314 C3
Sealing	: Without Bearing Seal	Without Bearing Seal
Lubrication interval	: 14418 h	14418 h
Lubricant amount	: 27 g	27 g
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	06/02/2024		1 / 2	

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : ODP NEMA Premium Efficiency Three-Phase

Product code : 12101776



Performance : 575 V 60 Hz 2P

Rated current : 130 A  
 LRC : 6.6  
 Rated torque : 30.6 kgfm  
 Locked rotor torque : 190 %  
 Breakdown torque : 250 %  
 Rated speed : 3555 rpm

Moment of inertia (J) : 0.5023 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.15  
 Temperature rise : 105 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
		Page	Revision	
		2 / 2		