

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : ODP NEMA Premium Efficiency Three-Phase Product code : 12124810

Frame	: 444/5TS	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 200 HP (150 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 182 A	Protection degree	: IP23
L. R. Amperes	: 1186 A	Cooling method	: IC01 - ODP
LRC	: 6.5x(Code G)	Mounting	: F-1
No load current	: 51.2 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3575 rpm	Noise level ²	: 88.0 dB(A)
Slip	: 0.69 %	Starting method	: Direct On Line
Rated torque	: 40.6 kgfm	Approx. weight ³	: 614 kg
Locked rotor torque	: 190 %		
Breakdown torque	: 250 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 1.08 kgm ²		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	93.0	93.6	94.5	95.0	Max. traction	: 581 kgf
Power Factor	0.55	0.79	0.85	0.87	Max. compression	: 1194 kgf

	<u>Drive end</u>	<u>Non drive end</u>
Bearing type	: 6314 C3	6314 C3
Sealing	: Without Bearing Seal	Without Bearing Seal
Lubrication interval	: 14418 h	14418 h
Lubricant amount	: 27 g	27 g
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : ODP NEMA Premium Efficiency Three-Phase

Product code : 12124810



Performance : 575 V 60 Hz 2P

Rated current : 182 A
 LRC : 6.5
 Rated torque : 40.6 kgfm
 Locked rotor torque : 190 %
 Breakdown torque : 250 %
 Rated speed : 3575 rpm

Moment of inertia (J) : 1.08 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	06/02/2024			