

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 Tru-Metric IE3 Three-Phase Product code : 12207019

Frame	: 280S/M	Locked rotor time	: 28s (cold) 16s (hot)
Output	: 200 HP (150 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 184 A	Protection degree	: IP55
L. R. Amperes	: 1178 A	Cooling method	: IC411 - TEFC
LRC	: 6.4	Mounting	: B35L(E)
No load current	: 56.4 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 1782 rpm	Starting method	: Direct On Line
Slip	: 1.00 %	Approx. weight <sup>3</sup>	: 861 kg
Rated torque	: 81.5 kgfm		
Locked rotor torque	: 229 %		
Breakdown torque	: 229 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 3.21 kgm <sup>2</sup>		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	95.4	96.2	96.2	Max. traction	: 1209 kgf
Power Factor	0.00	0.73	0.82	0.85	Max. compression	: 2070 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
3.9	3.2	2.9	1.9	1.3	0.8	0.5

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6316 C3	6316 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	10000 h	10000 h
Lubricant amount	:	34 g	34 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	14/01/2024		1 / 2	

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 Tru-Metric IE3 Three-Phase

Product code : 12207019



Performance : 575 V 60 Hz 4P

Rated current : 184 A  
 LRC : 6.4  
 Rated torque : 81.5 kgfm  
 Locked rotor torque : 229 %  
 Breakdown torque : 229 %  
 Rated speed : 1782 rpm

Moment of inertia (J) : 3.21 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.15  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	14/01/2024			