

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line		: Multimounting IE3 Three-Phase		Product code : 12233809		
Frame	: 132M		Locked rotor time	: 18s (cold) 10s (hot)		
Output	: 12.5 HP (9.2 kW)		Temperature rise	: 80 K		
Poles	: 4		Duty cycle	: S1		
Frequency	: 60 Hz		Ambient temperature	: -20°C to +40°C		
Rated voltage	: 230-460 V		Altitude	: 1000 m.a.s.l.		
Rated current	: 31.1-15.5 A		Protection degree	: IP55		
L. R. Amperes	: 271-135 A		Cooling method	: IC411 - TEFC		
LRC	: 8.7		Mounting	: B35L(E)		
No load current	: 15.0-7.50 A		Rotation ¹	: Both (CW and CCW)		
Rated speed	: 1765 rpm		Noise level ²	: 58.0 dB(A)		
Slip	: 1.94 %		Starting method	: Direct On Line		
Rated torque	: 5.14 kgfm		Approx. weight ³	: 74.0 kg		
Locked rotor torque	: 250 %					
Breakdown torque	: 380 %					
Insulation class	: F					
Service factor	: 1.00					
Moment of inertia (J)	: 0.0638 kgm ²					
Design	: N					
Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	89.7	91.0	91.7	Max. traction : 324 kgf	
Power Factor	0.00	0.62	0.74	0.81	Max. compression : 398 kgf	
			<u>Drive end</u>		<u>Non drive end</u>	
Bearing type	:	6308 ZZ		6207 ZZ		
Sealing	:	V'Ring		V'Ring		
Lubrication interval	:	0 h		0 h		
Lubricant amount	:	0 g		0 g		
Lubricant type	:	Mobil Polyrex EM				
Notes						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	24/10/2024				1 / 2	


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Multimounting IE3 Three-Phase Product code : 12233809



Performance : 230-460 V 60 Hz 4P

Rated current : 31.1-15.5 A
 LRC : 8.7
 Rated torque : 5.14 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 380 %
 Rated speed : 1765 rpm

Moment of inertia (J) : 0.0638 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	24/10/2024			