

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : Multimounting IE3 Three-Phase Product code : 12265212

Frame	: 132S	Locked rotor time	: 32s (cold) 18s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230-460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 18.1-9.07 A	Protection degree	: IP55
L. R. Amperes	: 189-94.3 A	Cooling method	: IC411 - TEFC
LRC	: 10.4	Mounting	: B35L(E)
No load current	: 8.86-4.43 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1775 rpm	Noise level ²	: 58.0 dB(A)
Slip	: 1.39 %	Starting method	: Direct On Line
Rated torque	: 3.08 kgfm	Approx. weight ³	: 64.8 kg
Locked rotor torque	: 260 %		
Breakdown torque	: 430 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0528 kgm ²		
Design	: N		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	88.5	91.0	91.7	Max. traction	: 211 kgf
Power Factor	0.65	0.77	0.83	Max. compression	: 276 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
8.7	6.6	6.0	5.2	3.3	2.5	1.6

	Drive end	Non drive end
Bearing type	: 6308 ZZ	: 6207 ZZ
Sealing	: V'Ring	: V'Ring
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	14/01/2024		1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : Multimounting IE3 Three-Phase

Product code : 12265212



Performance : 230-460 V 60 Hz 4P

Rated current : 18.1-9.07 A
 LRC : 10.4
 Rated torque : 3.08 kgfm
 Locked rotor torque : 260 %
 Breakdown torque : 430 %
 Rated speed : 1775 rpm

Moment of inertia (J) : 0.0528 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	14/01/2024			