

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 Close Coupled Pump JM NEMA Premium Efficiency Three-Phase      Product code : 12603920

Frame	: 254/6JM	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation <sup>1</sup>	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight <sup>3</sup>	: 134 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.1104 kgm <sup>2</sup>
Design	: B		

Output [HP]	15	10	10	10	15	15	15
Poles	4	4	4	4	4	4	4
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	36.0/18.0	15.2	14.8	14.5	21.5	20.5	20.0
L. R. Amperes [A]	230/115	109	115	120	105	111	118
LRC [A]	6.4x(Code G)	7.2x(Code J)	7.8x(Code J)	8.3x(Code K)	4.9x(Code E)	5.4x(Code F)	5.9x(Code G)
No load current [A]	14.0/7.00	6.70	7.10	7.40	7.10	7.60	7.40
Rated speed [RPM]	1768	1475	1480	1480	1455	1460	1465
Slip [%]	1.78	1.67	1.33	1.33	3.00	2.67	2.33
Rated torque [kgfm]	6.16	4.92	4.90	4.90	7.48	7.46	7.43
Locked rotor torque [%]	240	250	280	310	160	200	210
Breakdown torque [%]	260	300	340	370	200	220	240
Service factor	1.25	1.25	1.25	1.25	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	80 K	80 K	80 K
Locked rotor time	55s (cold) 31s (hot)	72s (cold) 40s (hot)	63s (cold) 35s (hot)	57s (cold) 32s (hot)	41s (cold) 23s (hot)	41s (cold) 23s (hot)	37s (cold) 21s (hot)
Noise level <sup>2</sup>	64.0 dB(A)	61.0 dB(A)	61.0 dB(A)	61.0 dB(A)	61.0 dB(A)	61.0 dB(A)	61.0 dB(A)
Efficiency (%)	25%	90.2	88.5	88.1	87.6	90.8	90.8
	50%	91.0	88.8	88.6	88.3	91.0	91.0
	75%	91.7	90.3	90.3	90.3	90.2	91.0
	100%	92.4	90.4	90.6	90.8	90.2	91.0
Power Factor	25%	0.44	0.40	0.37	0.35	0.49	0.46
	50%	0.68	0.65	0.62	0.59	0.74	0.71
	75%	0.78	0.77	0.74	0.72	0.82	0.80
	100%	0.83	0.83	0.81	0.79	0.86	0.85

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	8.1	8.1	8.1	8.1	8.1	8.1
	P2 (0,5;1,0)	6.8	6.8	6.8	6.8	6.8	6.8
	P3 (0,25;1,0)	6.3	6.3	6.3	6.3	6.3	6.3
	P4 (0,9;0,5)	3.9	3.9	3.9	3.9	3.9	3.9
	P5 (0,5;0,5)	2.7	2.7	2.7	2.7	2.7	2.7
	P6 (0,5;0,25)	1.8	1.8	1.8	1.8	1.8	1.8
	P7 (0,25;0,25)	1.2	1.2	1.2	1.2	1.2	1.2

Bearing type	: 6309 C3	Non drive end	6209 C3	Foundation loads	Max. traction : 213 kgf	
	: V'Ring	V'Ring				Max. compression : 347 kgf
	: 20000 h	20000 h				
	: 13 g	9 g				
	: Mobil Polyrex EM					

This revision replaces and cancel the previous one, which must be eliminated.

(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	14/01/2024				1 / 9	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Notes  
USABLE @208V 39.8A SF 1.15 SFA 45.8A

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	14/01/2024		2 / 9	

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM NEMA  
Premium Efficiency Three-Phase

Product code : 12603920



Performance : 230/460 V 60 Hz 4P

Rated current : 36.0/18.0 A  
 LRC : 6.4  
 Rated torque : 6.16 kgfm  
 Locked rotor torque : 240 %  
 Breakdown torque : 260 %  
 Rated speed : 1768 rpm

Moment of inertia (J) : 0.1104 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.25  
 Temperature rise : 80 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		3 / 9		
Date		14/01/2024		

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM NEMA  
Premium Efficiency Three-Phase

Product code : 12603920



Performance : 380 V 50 Hz 4P IE3

Rated current : 15.2 A  
LRC : 7.2  
Rated torque : 4.92 kgfm  
Locked rotor torque : 250 %  
Breakdown torque : 300 %  
Rated speed : 1475 rpm

Moment of inertia (J) : 0.1104 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.25  
Temperature rise : 80 K  
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 9	Revision
Checked by				
Date	14/01/2024			

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM NEMA  
Premium Efficiency Three-Phase

Product code : 12603920



Performance : 400 V 50 Hz 4P IE3

Rated current : 14.8 A  
LRC : 7.8  
Rated torque : 4.90 kgfm  
Locked rotor torque : 280 %  
Breakdown torque : 340 %  
Rated speed : 1480 rpm

Moment of inertia (J) : 0.1104 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.25  
Temperature rise : 80 K  
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

# LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 Close Coupled Pump JM NEMA  
Premium Efficiency Three-Phase

Product code : 12603920

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 4P IE3

Rated current : 14.5 A  
LRC : 8.3  
Rated torque : 4.90 kgfm  
Locked rotor torque : 310 %  
Breakdown torque : 370 %  
Rated speed : 1480 rpm

Moment of inertia (J) : 0.1104 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.25  
Temperature rise : 80 K  
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM NEMA  
Premium Efficiency Three-Phase

Product code : 12603920



Performance : 380 V 50 Hz 4P IE2

Rated current : 21.5 A  
 LRC : 4.9  
 Rated torque : 7.48 kgfm  
 Locked rotor torque : 160 %  
 Breakdown torque : 200 %  
 Rated speed : 1455 rpm

Moment of inertia (J) : 0.1104 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM NEMA  
Premium Efficiency Three-Phase

Product code : 12603920



Performance : 400 V 50 Hz 4P IE2

Rated current : 20.5 A  
LRC : 5.4  
Rated torque : 7.46 kgfm  
Locked rotor torque : 200 %  
Breakdown torque : 220 %  
Rated speed : 1460 rpm

Moment of inertia (J) : 0.1104 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.00  
Temperature rise : 80 K  
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				



# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 Close Coupled Pump JM NEMA  
Premium Efficiency Three-Phase

Product code : 12603920



Performance : 415 V 50 Hz 4P IE2

Rated current : 20.0 A  
 LRC : 5.9  
 Rated torque : 7.43 kgfm  
 Locked rotor torque : 210 %  
 Breakdown torque : 240 %  
 Rated speed : 1465 rpm

Moment of inertia (J) : 0.1104 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
			Page	Revision
			9 / 9	