

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :				
Product line	: NEMA Premium Efficiency Three-Phase	Product code :	12674776	
Frame	: 213/5T	Cooling method	: IC01 - ODP	
Insulation class	: F	Mounting	: F-1	
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)	
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line	
Altitude	: 1000 m.a.s.l.	Approx. weight ²	: 56.0 kg	
Design	: B	Moment of inertia (J)	: 0.0196 kgm ²	
Output [HP]	10	10	10	
Poles	2	2	2	
Frequency [Hz]	60	50	50	
Rated voltage [V]	230/460	190-220/380	415	
Rated current [A]	24.0/12.0	29.0-25.0/14.5	13.3	
L. R. Amperes [A]	163/81.6	157-135/78.3	86.5	
LRC [A]	6.8x(Code H)	5.4x(Code F)	6.5x(Code G)	
No load current [A]	9.32/4.66	9.15-7.90/4.58	5.51	
Rated speed [RPM]	3535	2910	2930	
Slip [%]	1.81	3.00	2.33	
Rated torque [kgfm]	2.05	2.49	2.48	
Locked rotor torque [%]	200	150	180	
Breakdown torque [%]	280	210	250	
Service factor	1.15	1.15	1.15	
Temperature rise	80 K	80 K	80 K	
Locked rotor time	19s (cold) 11s (hot)	0s (cold) 0s (hot)	0s (cold) 0s (hot)	
Noise level ²	66.0 dB(A)	64.0 dB(A)	64.0 dB(A)	
Efficiency (%)	25%			
	50%	88.5	89.0	
	75%	89.5	89.1	
	100%	89.5	87.9	
Power Factor	25%			
	50%	0.74	0.73	
	75%	0.84	0.84	
	100%	0.88	0.89	
Bearing type	: Drive end 6208 ZZ Non drive end 6206 ZZ	Foundation loads		
Sealing	: Without Bearing Seal Without Bearing Seal	Max. traction	: 86 kgf	
		Max. compression	: 142 kgf	
Lubrication interval	: -			
Lubricant amount	: -			
Lubricant type	: Mobil Polyrex EM			
Notes USABLE @208V 26.5A SF 1.00 SFA 26.5A				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/05/2022		1 / 4	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : NEMA Premium Efficiency Three-Phase Product code : 12674776

LOAD PERFORMANCE CURVE



Performance : 230/460 V 60 Hz 2P

Rated current : 24.0/12.0 A
 LRC : 6.8
 Rated torque : 2.05 kgfm
 Locked rotor torque : 200 %
 Breakdown torque : 280 %
 Rated speed : 3535 rpm

Moment of inertia (J) : 0.0196 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 4	Revision
Checked by				
Date	13/05/2022			


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : NEMA Premium Efficiency Three-Phase Product code : 12674776



Performance : 190-220/380 V 50 Hz 2P

Rated current : 29.0-25.0/14.5 A
 LRC : 5.4
 Rated torque : 2.49 kgfm
 Locked rotor torque : 150 %
 Breakdown torque : 210 %
 Rated speed : 2910 rpm

Moment of inertia (J) : 0.0196 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : NEMA Premium Efficiency Three-Phase Product code : 12674776

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 2P

Rated current	: 13.3 A	Moment of inertia (J)	: 0.0196 kgm ²
LRC	: 6.5	Duty cycle	: Cont.(S1)
Rated torque	: 2.48 kgfm	Insulation class	: F
Locked rotor torque	: 180 %	Service factor	: 1.15
Breakdown torque	: 250 %	Temperature rise	: 80 K
Rated speed	: 2930 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				