

DATA SHEETPRELIMINARY
DOCUMENT**Three Phase Induction Motor - Squirrel Cage**

Customer :

Product line : W01 - TEFC - Nema Premium Efficiency
Product code : 12675398

Frame	: 213/5T	Locked rotor time	: 16 s (hot) 29 s (cold)
Output	: 10 HP (7.5 kW)	Temperature rise ⁴	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l
Rated current	: 9.49 A	Protection degree	: IP55
L. R. Amperes	: 71.2 A	Cooling method	: IC411 - TEFC
LRC	: 7.5 Code H	Mounting	: F-1/B3R(D)
No load current	: 3.44 A	Rotation ¹	: Both
Rated speed	: 3530 rpm	Noise level ²	: 70 dB(A)
Slip	: 1.94 %	Starting method	: Direct On Line
Rated torque	: 2.06 kgfm	Approx. weight ³	: 73.2 kg
Locked rotor torque	: 260 %	Design	: B
Pull up torque	: 210 %		
Breakdown torque	: 300 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0303 kgm ²		

Output	Start	50%	75%	100%	Load type	: -
Efficiency (%)	-	89.5	90.2	90.2	Load torque	: -
Power Factor	0.56	0.75	0.84	0.88	Load inertia (J=GD ² /4)	: -

	Drive end	Non drive end
Bearing type	6208-ZZ	6206-ZZ
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	MOBIL POLYREX EM	

Notes:

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
9.55	7.67	7.49	5.36	3.42	2.47	1.67

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..

(1) Looking the motor from the shaft end.

(2) Measured at 1m and with tolerance of +0dB(A).

(3) Approximate weight, subject to be changed after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	2026/10/17			Page 1/2	Revision 0

LOAD PERFORMANCE CURVE


PRELIMINARY
DOCUMENT



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W01 - TEFC - Nema Premium Efficiency
Product code : 12675398



Performance : 10 HP (7.5 kW) 575V 60Hz 2P 213/5T

Rated current	: 9.49 A	Moment of inertia (J)	: 0.0303 kgm ²
LRC	: 7.5 Code H	Duty cycle	: Cont.(S1)
Rated torque	: 2.06 kgfm	Insulation class	: F
Locked rotor torque	: 260 %	Service factor	: 1.15
Breakdown torque	: 300 %	Temperature rise	: 80 K
Rated speed	: 3530 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 2/2 Revision 0			
Checked by					
Date	2026/10/17				