

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: NEMA Premium Efficiency Three-Phase	Product code :	12675410
Frame	: 182/4T	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 31.4 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.0118 kgm ²
Design	: B		
Output [HP]	1.5	1.5	1.5
Poles	6	6	6
Frequency [Hz]	60	50	50
Rated voltage [V]	230/460	190/380	220/415
Rated current [A]	4.44/2.22	5.18/2.59	4.73/2.51
L. R. Amperes [A]	30.6/15.3	29.5/14.8	29.8/15.8
LRC [A]	6.9x(Code K)	5.7x(Code H)	6.3x(Code J)
No load current [A]	2.73/1.36	2.69/1.34	2.74/1.46
Rated speed [RPM]	1170	955	960
Slip [%]	2.50	4.50	4.00
Rated torque [kgfm]	0.930	1.14	1.13
Locked rotor torque [%]	240	190	220
Breakdown torque [%]	340	260	290
Service factor	1.15	1.15	1.15
Temperature rise	80 K	80 K	80 K
Locked rotor time	99s (cold) 55s (hot)	0s (cold) 0s (hot)	0s (cold) 0s (hot)
Noise level ²	52.0 dB(A)	50.0 dB(A)	50.0 dB(A)
Efficiency (%)	25%	82.8	83.2
	50%	84.0	83.5
	75%	86.5	85.5
	100%	87.5	85.4
Power Factor	25%	0.29	0.31
	50%	0.50	0.54
	75%	0.63	0.66
	100%	0.71	0.74
Bearing type	: <u>Drive end</u> 6206 ZZ	<u>Non drive end</u> 6205 ZZ	Foundation loads
Sealing	: V'Ring	Without Bearing Seal	Max. traction : 53 kgf
Lubrication interval	: -	-	Max. compression : 84 kgf
Lubricant amount	: -	-	
Lubricant type	: Mobil Polyrex EM		
Notes USABLE @208V 4.91A SF 1.00 SFA 4.91A			
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.	
Rev.	Changes Summary	Performed	Checked
			Date
Performed by			
Checked by			Page
Date	13/05/2022		Revision
			1 / 4

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : NEMA Premium Efficiency Three-Phase Product code : 12675410

LOAD PERFORMANCE CURVE



Performance : 230/460 V 60 Hz 6P

Rated current : 4.44/2.22 A
 LRC : 6.9
 Rated torque : 0.930 kgfm
 Locked rotor torque : 240 %
 Breakdown torque : 340 %
 Rated speed : 1170 rpm

Moment of inertia (J) : 0.0118 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 4	Revision
Checked by				
Date	13/05/2022			


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : NEMA Premium Efficiency Three-Phase Product code : 12675410



Performance : 190/380 V 50 Hz 6P

Rated current : 5.18/2.59 A
 LRC : 5.7
 Rated torque : 1.14 kgfm
 Locked rotor torque : 190 %
 Breakdown torque : 260 %
 Rated speed : 955 rpm

Moment of inertia (J) : 0.0118 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				
			3 / 4	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : NEMA Premium Efficiency Three-Phase Product code : 12675410

LOAD PERFORMANCE CURVE



Performance : 220/415 V 50 Hz 6P

Rated current	: 4.73/2.51 A	Moment of inertia (J)	: 0.0118 kgm ²
LRC	: 6.3	Duty cycle	: Cont.(S1)
Rated torque	: 1.13 kgfm	Insulation class	: F
Locked rotor torque	: 220 %	Service factor	: 1.15
Breakdown torque	: 290 %	Temperature rise	: 80 K
Rated speed	: 960 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 4	Revision
Checked by				
Date	13/05/2022			