

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :							
Product line	: W22 NEMA Premium Efficiency Three-Phase	Product code :	12717787				
Frame	: 213/5T	Cooling method	: IC411 - TEFC				
Insulation class	: F	Mounting	: F-1				
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)				
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line				
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 67.3 kg				
Protection degree	: IP55	Moment of inertia (J)	: 0.0197 kgm ²				
Design	: B						
Output [HP]	7.5	5.5	5.5	5.5	7.5	7.5	7.5
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	17.5/8.76	7.83	7.60	7.49	10.6	10.2	9.82
L. R. Amperes [A]	126/63.1	60.3	57.8	62.2	60.4	65.3	67.8
LRC [A]	7.2x(Code H)	7.7x(Code J)	7.6x(Code J)	8.3x(Code K)	5.7x(Code F)	6.4x(Code G)	6.9x(Code H)
No load current [A]	6.00/3.00	2.90	3.15	3.30	2.90	3.15	3.30
Rated speed [RPM]	3530	2940	2950	2955	2900	2915	2925
Slip [%]	1.94	2.00	1.67	1.50	3.33	2.83	2.50
Rated torque [kgfm]	1.54	1.36	1.35	1.35	1.88	1.87	1.86
Locked rotor torque [%]	210	220	250	270	170	180	200
Breakdown torque [%]	300	310	350	370	229	260	280
Service factor	1.25	1.25	1.25	1.25	1.25	1.25	1.25
Temperature rise	80 K	80 K	80 K	80 K	80 K	80 K	80 K
Locked rotor time	36s (cold) 20s (hot)	37s (cold) 21s (hot)	37s (cold) 21s (hot)	37s (cold) 21s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)
Noise level ²	68.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)
Efficiency (%)	25%						
	50%	87.5	86.7	86.4	86.1	88.5	87.5
	75%	89.5	88.2	88.3	88.5	88.5	87.5
	100%	89.5	88.2	88.3	88.5	87.5	88.5
Power Factor	25%						
	50%	0.75	0.74	0.70	0.67	0.80	0.77
	75%	0.84	0.83	0.81	0.78	0.87	0.86
	100%	0.88	0.88	0.86	0.84	0.90	0.89
Losses at normative operating points (speed;torque), in percentage of rated output power							
Losses (%)	P1 (0,9;1,0)	11.3	11.3	11.3	11.3	11.3	11.3
	P2 (0,5;1,0)	9.1	9.1	9.1	9.1	9.1	9.1
	P3 (0,25;1,0)	8.4	8.4	8.4	8.4	8.4	8.4
	P4 (0,9;0,5)	5.9	5.9	5.9	5.9	5.9	5.9
	P5 (0,5;0,5)	3.6	3.6	3.6	3.6	3.6	3.6
	P6 (0,5;0,25)	2.4	2.4	2.4	2.4	2.4	2.4
	P7 (0,25;0,25)	1.5	1.5	1.5	1.5	1.5	1.5
Bearing type	: Drive end : 6308 ZZ	Non drive end : 6207 ZZ	Foundation loads				
Sealing	: V'Ring	V'Ring	Max. traction	: 62 kgf			
Lubrication interval	: -	-	Max. compression	: 130 kgf			
Lubricant amount	: -	-					
Lubricant type	: Mobil Polyrex EM						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date	
Performed by							
Checked by						Page	Revision
Date	01/02/2024					1 / 9	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 19.4A SF 1.15 SFA 22.3A

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	01/02/2024		2 / 9	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12717787



Performance : 230/460 V 60 Hz 2P

Rated current : 17.5/8.76 A
 LRC : 7.2
 Rated torque : 1.54 kgfm
 Locked rotor torque : 210 %
 Breakdown torque : 300 %
 Rated speed : 3530 rpm

Moment of inertia (J) : 0.0197 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12717787



Performance : 380 V 50 Hz 2P IE3

Rated current : 7.83 A
 LRC : 7.7
 Rated torque : 1.36 kgfm
 Locked rotor torque : 220 %
 Breakdown torque : 310 %
 Rated speed : 2940 rpm

Moment of inertia (J) : 0.0197 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12717787



Performance : 400 V 50 Hz 2P IE3

Rated current : 7.60 A
 LRC : 7.6
 Rated torque : 1.35 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 350 %
 Rated speed : 2950 rpm

Moment of inertia (J) : 0.0197 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12717787



Performance : 415 V 50 Hz 2P IE3


Rated current : 7.49 A
 LRC : 8.3
 Rated torque : 1.35 kgfm
 Locked rotor torque : 270 %
 Breakdown torque : 370 %
 Rated speed : 2955 rpm

Moment of inertia (J) : 0.0197 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12717787



Performance : 380 V 50 Hz 2P IE2

Rated current : 10.6 A
 LRC : 5.7
 Rated torque : 1.88 kgfm
 Locked rotor torque : 170 %
 Breakdown torque : 229 %
 Rated speed : 2900 rpm

Moment of inertia (J) : 0.0197 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12717787



Performance : 400 V 50 Hz 2P IE2

Rated current : 10.2 A
 LRC : 6.4
 Rated torque : 1.87 kgfm
 Locked rotor torque : 180 %
 Breakdown torque : 260 %
 Rated speed : 2915 rpm

Moment of inertia (J) : 0.0197 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12717787



Performance : 415 V 50 Hz 2P IE2

Rated current : 9.82 A
 LRC : 6.9
 Rated torque : 1.86 kgfm
 Locked rotor torque : 200 %
 Breakdown torque : 280 %
 Rated speed : 2925 rpm

Moment of inertia (J) : 0.0197 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				
			9 / 9	