

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line : W22 Close Coupled Pump JM NEMA Premium Efficiency Three-Phase			Product code : 12736795			
Frame	: 213/5JM		Locked rotor time	: 104s (cold) 58s (hot)		
Output	: 3 HP (2.2 kW)		Temperature rise	: 80 K		
Poles	: 6		Duty cycle	: Cont.(S1)		
Frequency	: 60 Hz		Ambient temperature	: -20°C to +40°C		
Rated voltage	: 575 V		Altitude	: 1000 m.a.s.l.		
Rated current	: 3.53 A		Protection degree	: IP55		
L. R. Amperes	: 24.7 A		Cooling method	: IC411 - TEFC		
LRC	: 7.0x(Code K)		Mounting	: F-1		
No load current	: 2.20 A		Rotation <sup>1</sup>	: Both (CW and CCW)		
Rated speed	: 1175 rpm		Noise level <sup>2</sup>	: 55.0 dB(A)		
Slip	: 2.08 %		Starting method	: Direct On Line		
Rated torque	: 1.85 kgfm		Approx. weight <sup>3</sup>	: 72.7 kg		
Locked rotor torque	: 200 %					
Breakdown torque	: 280 %					
Insulation class	: F					
Service factor	: 1.25					
Moment of inertia (J)	: 0.0504 kgm <sup>2</sup>					
Design	: B					
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	86.5	88.5	89.5	Max. traction : 59 kgf		
Power Factor	0.50	0.63	0.70	Max. compression : 132 kgf		
Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.0	8.5	7.7	6.7	4.4	3.4	2.5
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	6309 Z C3		6207 ZZ		
Sealing	:	V'Ring		V'Ring		
Lubrication interval	:	20000 h		40000 h		
Lubricant amount	:	13 g		0 g		
Lubricant type	:	Mobil Polyrex EM				
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	13/01/2024				1 / 2	

# LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 Close Coupled Pump JM NEMA  
Premium Efficiency Three-Phase

Product code : 12736795

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 6P

Rated current : 3.53 A  
LRC : 7.0  
Rated torque : 1.85 kgfm  
Locked rotor torque : 200 %  
Breakdown torque : 280 %  
Rated speed : 1175 rpm

Moment of inertia (J) : 0.0504 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.25  
Temperature rise : 80 K  
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	13/01/2024			