

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :							
Product line		: W22 IEEE 841 NEMA Premium Efficiency Three-Phase			Product code : 12811471		
Frame	:	324/6T			Locked rotor time	:	36s (cold) 20s (hot)
Output	:	40 HP (30 kW)			Temperature rise	:	80 K
Poles	:	4			Duty cycle	:	Cont.(S1)
Frequency	:	60 Hz			Ambient temperature	:	-20°C to +40°C
Rated voltage	:	575 V			Altitude	:	1000 m.a.s.l.
Rated current	:	37.7 A			Protection degree	:	IP55
L. R. Amperes	:	230 A			Cooling method	:	IC411 - TEFC
LRC	:	6.1x(Code G)			Mounting	:	F-1
No load current	:	13.6 A			Rotation ¹	:	Both (CW and CCW)
Rated speed	:	1775 rpm			Noise level ²	:	66.0 dB(A)
Slip	:	1.39 %			Starting method	:	Direct On Line
Rated torque	:	16.4 kgfm			Approx. weight ³	:	264 kg
Locked rotor torque	:	229 %					
Breakdown torque	:	240 %					
Insulation class	:	F					
Service factor	:	1.25					
Moment of inertia (J)	:	0.3861 kgm ²					
Design	:	B					
Output	50%	75%	100%	Foundation loads			
Efficiency (%)	93.6	94.1	94.1	Max. traction			: 362 kgf
Power Factor	0.72	0.80	0.85	Max. compression			: 626 kgf
Losses at normative operating points (speed;torque), in percentage of rated output power							
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)	
6.1	5.1	4.9	2.8	1.9	1.2	0.8	
Bearing type			<u>Drive end</u>		<u>Non drive end</u>		
Sealing			6312 C3		6212 C3		
Lubrication interval			Taconite Labyrinth		Taconite Labyrinth		
Lubricant amount			20000 h		20000 h		
Lubricant type			21 g		13 g		
			Mobil Polyrex EM				
Notes:							
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date	
Performed by							
Checked by					Page	Revision	
Date	13/01/2024				1 / 2		


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 12811471



Performance : 575 V 60 Hz 4P

Rated current	: 37.7 A	Moment of inertia (J)	: 0.3861 kgm ²
LRC	: 6.1	Duty cycle	: Cont.(S1)
Rated torque	: 16.4 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.25
Breakdown torque	: 240 %	Temperature rise	: 80 K
Rated speed	: 1775 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	13/01/2024			