

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 P Base NEMA Premium Efficiency Three-Phase Product code : 13129041

Frame	: 364/5HP	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: W-6
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 432 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.9798 kgm ²
Design	: B		

Output [HP]	75	60	60	60	75	75	75
Poles	4	4	4	4	4	4	4
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	174/87.2	88.5	84.9	82.7	106	102	98.7
L. R. Amperes [A]	1116/558	620	637	662	541	571	602
LRC [A]	6.4x(Code G)	7.0x(Code H)	7.5x(Code J)	8.0x(Code J)	5.1x(Code E)	5.6x(Code F)	6.1x(Code G)
No load current [A]	66.0/33.0	33.0	35.0	38.0	33.0	35.0	38.0
Rated speed [RPM]	1780	1480	1480	1485	1470	1475	1480
Slip [%]	1.11	1.33	1.33	1.00	2.00	1.67	1.33
Rated torque [kgfm]	30.6	29.4	29.4	29.3	37.0	36.9	36.8
Locked rotor torque [%]	240	210	240	260	170	200	210
Breakdown torque [%]	260	250	280	310	200	220	240
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	25s (cold) 14s (hot)	18s (cold) 10s (hot)	18s (cold) 10s (hot)	18s (cold) 10s (hot)	18s (cold) 10s (hot)	18s (cold) 10s (hot)	18s (cold) 10s (hot)
Noise level ²	67.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)
Efficiency (%)	25%	0.000			0.000		
	50%	94.5	93.7	93.6	93.5	94.5	94.1
	75%	95.0	94.2	94.2	94.2	94.1	94.5
	100%	95.4	94.2	94.4	94.6	93.6	94.1
Power Factor	25%	0.00			0.00		
	50%	0.68	0.68	0.64	0.61	0.75	0.67
	75%	0.78	0.78	0.75	0.73	0.82	0.78
	100%	0.83	0.82	0.81	0.80	0.84	0.82

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	4.7	4.7	4.7	4.7	4.7	4.7	4.7
	P2 (0,5;1,0)	3.8	3.8	3.8	3.8	3.8	3.8	3.8
	P3 (0,25;1,0)	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	P4 (0,9;0,5)	2.4	2.4	2.4	2.4	2.4	2.4	2.4
	P5 (0,5;0,5)	1.6	1.6	1.6	1.6	1.6	1.6	1.6
	P6 (0,5;0,25)	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	P7 (0,25;0,25)	0.7	0.7	0.7	0.7	0.7	0.7	0.7

Bearing type	: Drive end	6316 C3	Non drive end	6314 C3	Foundation loads Max. traction Max. compression
	: Sealing	Lip Seal	Lip Seal		
	: Lubrication interval	5000 h	6000 h		
	: Lubricant amount	34 g	27 g		
	: Lubricant type	Mobil Polyrex EM			

This revision replaces and cancel the previous one, which must be eliminated.

(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	22/10/2023		1 / 9	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 186A SF 1.10 SFA 205A

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	22/10/2023		2 / 9	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium Efficiency Three-Phase

Product code : 13129041



Performance : 230/460 V 60 Hz 4P

Rated current : 174/87.2 A
 LRC : 6.4
 Rated torque : 30.6 kgfm
 Locked rotor torque : 240 %
 Breakdown torque : 260 %
 Rated speed : 1780 rpm

Moment of inertia (J) : 0.9798 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 P Base NEMA Premium Efficiency
Three-Phase

Product code : 13129041



Performance : 380 V 50 Hz 4P IE3

Rated current : 88.5 A
 LRC : 7.0
 Rated torque : 29.4 kgfm
 Locked rotor torque : 210 %
 Breakdown torque : 250 %
 Rated speed : 1480 rpm

Moment of inertia (J) : 0.9798 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 9	Revision
Checked by				
Date	22/10/2023			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 P Base NEMA Premium Efficiency
Three-Phase

Product code : 13129041



Performance : 400 V 50 Hz 4P IE3

Rated current : 84.9 A
 LRC : 7.5
 Rated torque : 29.4 kgfm
 Locked rotor torque : 240 %
 Breakdown torque : 280 %
 Rated speed : 1480 rpm

Moment of inertia (J) : 0.9798 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 5 / 9	Revision
Checked by				
Date	22/10/2023			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium Efficiency
Three-Phase

Product code : 13129041



Performance : 415 V 50 Hz 4P IE3

Rated current : 82.7 A
 LRC : 8.0
 Rated torque : 29.3 kgfm
 Locked rotor torque : 260 %
 Breakdown torque : 310 %
 Rated speed : 1485 rpm

Moment of inertia (J) : 0.9798 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 6 / 9	Revision
Checked by				
Date	22/10/2023			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium Efficiency Three-Phase

Product code : 13129041



Performance : 380 V 50 Hz 4P IE2

Rated current : 106 A
 LRC : 5.1
 Rated torque : 37.0 kgfm
 Locked rotor torque : 170 %
 Breakdown torque : 200 %
 Rated speed : 1470 rpm

Moment of inertia (J) : 0.9798 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 105 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium Efficiency Three-Phase

Product code : 13129041



Performance : 400 V 50 Hz 4P IE2

Rated current : 102 A
 LRC : 5.6
 Rated torque : 36.9 kgfm
 Locked rotor torque : 200 %
 Breakdown torque : 220 %
 Rated speed : 1475 rpm

Moment of inertia (J) : 0.9798 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 105 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 8 / 9	Revision
Checked by				
Date	22/10/2023			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium Efficiency
Three-Phase

Product code : 13129041



Performance : 415 V 50 Hz 4P IE2

Rated current : 98.7 A
 LRC : 6.1
 Rated torque : 36.8 kgfm
 Locked rotor torque : 210 %
 Breakdown torque : 240 %
 Rated speed : 1480 rpm

Moment of inertia (J) : 0.9798 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 105 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				