

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line : W22 P Base NEMA Premium Efficiency Three-Phase			Product code :		13389666	
Frame	: 213HP		Locked rotor time	: 36s (cold) 20s (hot)		
Output	: 7.5 HP (5.5 kW)		Temperature rise	: 80 K		
Poles	: 4		Duty cycle	: Cont.(S1)		
Frequency	: 60 Hz		Ambient temperature	: -20°C to +40°C		
Rated voltage	: 575 V		Altitude	: 1000 m.a.s.l.		
Rated current	: 7.34 A		Protection degree	: IP55		
L. R. Amperes	: 52.1 A		Cooling method	: IC411 - TEFC		
LRC	: 7.1x(Code H)		Mounting	: W-6		
No load current	: 3.36 A		Rotation ¹	: Both (CW and CCW)		
Rated speed	: 1765 rpm		Noise level ²	: 58.0 dB(A)		
Slip	: 1.94 %		Starting method	: Direct On Line		
Rated torque	: 3.08 kgfm		Approx. weight ³	: 75.8 kg		
Locked rotor torque	: 220 %					
Breakdown torque	: 310 %					
Insulation class	: F					
Service factor	: 1.25					
Moment of inertia (J)	: 0.0566 kgm ²					
Design	: B					
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	89.5	91.0	91.7	Max. traction		
Power Factor	0.66	0.76	0.82	Max. compression		
Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
8.8	7.0	6.5	4.9	3.3	2.4	1.6
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	6309 ZZ		6207 ZZ		
Sealing	:	V'Ring		V'Ring		
Lubrication interval	:	-		-		
Lubricant amount	:	-		-		
Lubricant type	:	Mobil Polyrex EM				
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	14/01/2024				1 / 2	

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 P Base NEMA Premium Efficiency
Three-Phase

Product code : 13389666

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 4P

Rated current : 7.34 A
 LRC : 7.1
 Rated torque : 3.08 kgfm
 Locked rotor torque : 220 %
 Breakdown torque : 310 %
 Rated speed : 1765 rpm

Moment of inertia (J) : 0.0566 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	14/01/2024			