

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :		
Product line	: NEMA Premium Efficiency Three-Phase	
Product code :	13484505	
Frame	: 182/4TC	
Insulation class	: F	
Duty cycle	: Cont.(S1)	
Ambient temperature	: -20°C to +40°C	
Altitude	: 1000 m.a.s.l.	
Design	: B	
Cooling method	: IC01 - ODP	
Mounting	: W-6	
Rotation ¹	: Both (CW and CCW)	
Starting method	: Direct On Line	
Approx. weight ³	: 33.9 kg	
Moment of inertia (J)	: 0.0130 kgm ²	
Output [HP]	3	
Poles	4	
Frequency [Hz]	60	
Rated voltage [V]	230/460	
Rated current [A]	7.72/3.86	
L. R. Amperes [A]	64.8/32.4	
LRC [A]	8.4x(Code K)	
No load current [A]	4.14/2.07	
Rated speed [RPM]	1765	
Slip [%]	1.94	
Rated torque [kgfm]	1.23	
Locked rotor torque [%]	220	
Breakdown torque [%]	330	
Service factor	1.15	
Temperature rise	80 K	
Locked rotor time	27s (cold) 15s (hot)	
Noise level ²	55.0 dB(A)	
Efficiency (%)	25%	
	50%	87.5
	75%	88.5
	100%	89.5
Power Factor	25%	
	50%	0.60
	75%	0.73
	100%	0.80
Bearing type	: Drive end 6206 ZZ Non drive end 6205 ZZ	
Sealing	: Without Without Bearing Seal Bearing Seal	
Lubrication interval	: - -	
Lubricant amount	: - -	
Lubricant type	: Mobil Polyrex EM	
Foundation loads	Max. traction : 76 kgf	
	Max. compression : 110 kgf	
Notes		
USABLE @208V 8.54A SF 1.00 SFA 8.54A		
This revision replaces and cancel the previous one, which must be eliminated.		
(1) Looking the motor from the shaft end.		
(2) Measured at 1m and with tolerance of +3dB(A).		
(3) Approximate weight subject to changes after manufacturing process.		
(4) At 100% of full load.		
These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary	
Performed by	Performed	
Checked by	Checked	
Date	13/05/2022	
Page	1 / 4	
Revision		

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : NEMA Premium Efficiency Three-Phase Product code : 13484505

LOAD PERFORMANCE CURVE



Performance : 230/460 V 60 Hz 4P

Rated current : 7.72/3.86 A
 LRC : 8.4
 Rated torque : 1.23 kgfm
 Locked rotor torque : 220 %
 Breakdown torque : 330 %
 Rated speed : 1765 rpm

Moment of inertia (J) : 0.0130 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 4	Revision
Checked by				
Date	13/05/2022			


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : NEMA Premium Efficiency Three-Phase Product code : 13484505



Performance : 190-220/380 V 50 Hz 4P

Rated current : 9.08-7.84/4.54 A
 LRC : 6.4
 Rated torque : 1.49 kgfm
 Locked rotor torque : 150 %
 Breakdown torque : 240 %
 Rated speed : 1460 rpm

Moment of inertia (J) : 0.0130 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : NEMA Premium Efficiency Three-Phase Product code : 13484505

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 4P

Rated current	: 4.33 A	Moment of inertia (J)	: 0.0130 kgm ²
LRC	: 7.5	Duty cycle	: Cont.(S1)
Rated torque	: 1.48 kgfm	Insulation class	: F
Locked rotor torque	: 180 %	Service factor	: 1.15
Breakdown torque	: 300 %	Temperature rise	: 80 K
Rated speed	: 1470 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 4	Revision
Checked by				
Date	13/05/2022			