

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :					
Product line		: W22 NEMA Premium Efficiency Three-Phase		Product code : 13500649	
Frame	: 586/7TZ		Locked rotor time	: 63s (cold) 35s (hot)	
Output	: 300 HP (220 kW)		Temperature rise	: 80 K	
Frequency	: 60 Hz		Duty cycle	: Cont.(S1)	
Rated voltage	: 575 V		Ambient temperature	: -20°C to +40°C	
Poles	: 4		Altitude	: 1000 m.a.s.l.	
Rated current	: 280 A		Protection degree	: IP55	
	: 7.2x(Code H)		Cooling method	: IC411 - TEFC	
Rated speed	: 1791 rpm		Mounting	: F-1	
Rated torque	: 122 kgfm		Rotation ¹	: Both (CW and CCW)	
Insulation class	: F		Noise level ²	: 78.0 dB(A)	
Service factor	: 1.15		Starting method	: Direct On Line	
Moment of inertia (J)	: 5.92 kgm ²		Approx. weight ³	: 1397 kg	
Design	: A				
Output	25%	50%	75%	100%	
Efficiency (%)	0.000	95.4	95.8	96.2	
Power Factor	0.00	0.70	0.80	0.82	
Foundation loads					
Max. traction		: 1465 kgf			
Max. compression		: 2862 kgf			
Bearing type		Drive end	Non drive end		
:		NU-324 C3	6319 C3		
Sealing		Taconite Labyrinth		Taconite Labyrinth	
Lubrication interval		3000 h		8000 h	
Lubricant amount		72 g		45 g	
Lubricant type		Mobil Polyrex EM			
Notes					
W22 Crusher Duty - NEMA Premium Efficiency					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/05/2026			1 / 3	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	28/05/2026		2 / 3	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 13500649



Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		Revision
Checked by				
Date				