

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line		: W22 IEEE 841 NEMA Premium Efficiency Three-Phase		Product code :		1355559
Frame	:	586/7T		Locked rotor time	:	54s (cold) 30s (hot)
Output	:	250 HP (185 kW)		Temperature rise	:	80 K
Poles	:	6		Duty cycle	:	Cont.(S1)
Frequency	:	60 Hz		Ambient temperature	:	-20°C to +40°C
Rated voltage	:	575 V		Altitude	:	1000 m.a.s.l.
Rated current	:	239 A		Protection degree	:	IP55
L. R. Amperes	:	1459 A		Cooling method	:	IC411 - TEFC
LRC	:	6.1x(Code G)		Mounting	:	F-1
No load current	:	96.0 A		Rotation <sup>1</sup>	:	Both (CW and CCW)
Rated speed	:	1192 rpm		Noise level <sup>2</sup>	:	77.0 dB(A)
Slip	:	0.67 %		Starting method	:	Direct On Line
Rated torque	:	152 kgfm		Approx. weight <sup>3</sup>	:	1584 kg
Locked rotor torque	:	190 %				
Breakdown torque	:	210 %				
Insulation class	:	F				
Service factor	:	1.25				
Moment of inertia (J)	:	9.53 kgm <sup>2</sup>				
Design	:	B				
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	95.0	95.4	95.8	Max. traction : 1396 kgf		
Power Factor	0.68	0.77	0.81	Max. compression : 2980 kgf		
Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.7	3.4	2.7	2.9	1.8	1.4	0.8
			<u>Drive end</u>	<u>Non drive end</u>		
Bearing type	:	NU-322 C3		6319 C3		
Sealing	:	Inpro/Seal		Inpro/Seal		
Lubrication interval	:	7000 h		13000 h		
Lubricant amount	:	60 g		45 g		
Lubricant type	:	Mobil Polyrex EM				
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	13/01/2024				1 / 3	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

### Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/01/2024		2 / 3	

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 IEEE 841 NEMA Premium Efficiency  
Three-Phase

Product code : 1355559



Performance : 575 V 60 Hz 6P

Rated current : 239 A  
 LRC : 6.1  
 Rated torque : 152 kgfm  
 Locked rotor torque : 190 %  
 Breakdown torque : 210 %  
 Rated speed : 1192 rpm

Moment of inertia (J) : 9.53 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.25  
 Temperature rise : 80 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		3 / 3		
Date		13/01/2024		