

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line		: W22 IEEE 841 NEMA Premium Efficiency Three-Phase			Product code : 13584918	
Frame	:	182/4TC		Locked rotor time	:	55s (cold) 31s (hot)
Output	:	2 HP (1.5 kW)		Temperature rise	:	80 K
Poles	:	6		Duty cycle	:	Cont.(S1)
Frequency	:	60 Hz		Ambient temperature	:	-20°C to +40°C
Rated voltage	:	575 V		Altitude	:	1000 m.a.s.l.
Rated current	:	2.58 A		Protection degree	:	IP55
L. R. Amperes	:	19.3 A		Cooling method	:	IC411 - TEFC
LRC	:	7.5x(Code L)		Mounting	:	F-1
No load current	:	1.52 A		Rotation ¹	:	Both (CW and CCW)
Rated speed	:	1170 rpm		Noise level ²	:	52.0 dB(A)
Slip	:	2.50 %		Starting method	:	Direct On Line
Rated torque	:	1.24 kgfm		Approx. weight ³	:	52.0 kg
Locked rotor torque	:	300 %				
Breakdown torque	:	350 %				
Insulation class	:	F				
Service factor	:	1.25				
Moment of inertia (J)	:	0.0262 kgm ²				
Design	:	B				
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	86.5	87.5	88.5	Max. traction : 65 kgf		
Power Factor	0.46	0.58	0.66	Max. compression : 117 kgf		
Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
12.3	9.8	9.2	7.4	5.0	3.9	2.9
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	6207 C3		6206 C3		
Sealing	:	Inpro/Seal		Inpro/Seal		
Lubrication interval	:	20000 h		20000 h		
Lubricant amount	:	7 g		5 g		
Lubricant type	:	Mobil Polyrex EM				
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	13/01/2024				1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 13584918

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 6P

Rated current : 2.58 A	Moment of inertia (J) : 0.0262 kgm ²
LRC : 7.5	Duty cycle : Cont.(S1)
Rated torque : 1.24 kgfm	Insulation class : F
Locked rotor torque : 300 %	Service factor : 1.25
Breakdown torque : 350 %	Temperature rise : 80 K
Rated speed : 1170 rpm	Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	13/01/2024			