DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: Special Motor
Product code	: 13827808

Frame	: 586/7TZ
Output	: 350 HP (260 kW)
Poles	: 4
Frequency	: 60 Hz
Rated voltage	: 575 V
Rated current	: 327 A
L. R. Amperes	: 2450 A
LRC	: 7.5
No load current	: 111 A
Rated speed	: 1792 rpm
Slip	: 0.44 %
Rated torque	: 142 kgfm
Locked rotor torque	: 250 %
Pull up torque	: 210 %
Breakdown torque	: 270 %
Insulation class	: F
Service factor	: 1.15
Moment of inertia (J)	: 7.49 kgm²

Locked rotor time	: 25 s (hot) 45 s (cold)
Temperature rise[4]	: 80 K
Duty cycle	: S1
Ambient temperature	: -20 °C to +40 °C
Altitude	: 1000 m.a.s.l
Protection degree	: IP55
Cooling method	: IC411 - TEFC
Mounting	: B3R(D)
Rotation[1]	: Both
Noise level[2]	: 78 dB(A)
Starting method	: Direct On Line
Approx. weight[3]	: 1567 kg
Design	: A

Output	Start	50%	75%	100%
Efficiency (%)	-	95.4	96.2	96.2
Power Factor	0.00	0.68	0.79	0.83

Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

	Drive end	Non drive end
Bearing type	NU-324-C3	6319-C3
Lubrication interval	3000 h	8000 h
Lubrication amount	72 g	45 g
Lubricant type	MOBIL POLYREX EM	

Notes:
W22 NEMA Premium Efficiency
Crusher Duty
The vibration and noise level informed are valid when motor is operating with roller bearings respecting their minimum radial load. Thus, WEG reserves the right to test the motor with ball bearings.

Standards

Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				16/06/2026


Performed by	harlei		226103/2016	
Checked by	AUTOMATICO		Page	Revision
Date	16/06/2026		1/2	2

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: Special Motor
Product code	: 13827808



Performance	: 350 HP (260 kW) 575V 60Hz 4P 586/7TZ

Rated current	: 327 A	Moment of inertia (J)	: 7.49 kgm²
LRC	: 7.5	Duty cycle	: Cont.(S1)
Rated torque	: 142 kgfm	Insulation class	: F
Locked rotor torque	: 250 %	Service factor	: 1.15
Breakdown torque	: 270 %	Temperature rise	: 80 K
Rated speed	: 1792 rpm	Design	: A

Rev.	Changes Summary	Performed	Checked	Date
				16/06/2026

Performed by	harlei		226103/2016	
Checked by	AUTOMATICO		Page	Revision
Date	16/06/2026		2/2	2

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.