

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer	:			
Product line	: Standard Efficiency Three-Phase	Product code : 13880823		
Frame	: W56C	Cooling method : IC411 - TEFC		
Insulation class	: F	Mounting : F-1		
Duty cycle	: Cont.(S1)	Rotation <sup>1</sup> : Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method : Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight <sup>3</sup> : 7.3 kg		
Protection degree	: IP55	Moment of inertia (J) : 0.0013 kgm <sup>2</sup>		
Output [HP]		0.33		
Poles		4		
Frequency [Hz]		60		
Rated voltage [V]		575		
Rated current [A]		0.527		
L. R. Amperes [A]		2.85		
LRC [A]		5.4x(Code K)		
No load current [A]		0.426		
Rated speed [RPM]		1730		
Slip [%]		3.89		
Rated torque [kgfm]		0.138		
Locked rotor torque [%]		229		
Breakdown torque [%]		270		
Service factor		1.15		
Temperature rise		80 K		
Locked rotor time		37s (cold) 21s (hot)		
Noise level <sup>2</sup>		50.0 dB(A)		
Efficiency (%)	25%			
	50%	57.5		
	75%	64.0		
	100%	68.0		
Power Factor	25%			
	50%	0.48		
	75%	0.60		
	100%	0.70		
Bearing type	: <u>Drive end</u> 6203 ZZ <u>Non drive end</u> 6202 ZZ	Foundation loads		
Sealing	: V'Ring                    V'Ring	Max. traction : 8 kgf		
Lubrication interval	: -                                -	Max. compression : 15 kgf		
Lubricant amount	: -                                -			
Lubricant type	: Mobil Polyrex EM			
Notes				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/05/2022		1 / 2	

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Standard Efficiency Three-Phase      Product code : 13880823

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 4P

Rated current : 0.527 A  
 LRC : 5.4  
 Rated torque : 0.138 kgfm  
 Locked rotor torque : 229 %  
 Breakdown torque : 270 %  
 Rated speed : 1730 rpm

Moment of inertia (J) : 0.0013 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.15  
 Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	13/05/2022			